



**Globally Proven
Construction Solutions**

E-CON™

E-CON™ is a concentrated, odourless, water-based liquid polymer, that when placed on fresh concrete, helps to control the rate of evaporation and extend workability. When applied to fresh concrete, E-CON reduces contractor field problems with exposed exterior concrete by minimizing surface crusting and plastic shrinkage cracks. E-CON is ideal for achieving superior quality flatwork in challenging conditions such as high and low temperatures, low humidity, high winds, and direct sunlight. Proper placement of E-CON is aided by the presence of a dissipating pink dye.



FEATURES/BENEFITS

- Effective evaporation control
- Improves workability of freshly placed concrete
- Reduces plastic shrinkage cracks
- Reduces evaporation rates up to 80% in wind and 40% in hot sunlight
- Water based; low odour
- Remains effective after screeding and first floating operation
- Non-residual
- Economically concentrated

SUITABLE SUBSTRATES

- Freshly Placed Concrete

USES

E-CON aids workability with standard concrete mixes, silica fume concrete, thin concrete resurfacing, and all cementitious shake on floor hardeners after placement by protecting against moisture loss. The protective shield formed usually lasts as long as the concrete remains workable, despite successive floating and troweling operations. No residue or colour remains after the concrete hardens.

PACKAGING

- 1 Litre
- 3.8 Litre
- 18.9 Litre
- 208 Litre
- 1040 Litre

MANUFACTURER

LATICRETE Australia Pty Ltd
29 Telford Street
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599
Toll Free: 1800 331 012
Fax: 07 3865 2250
Internet: www.laticrete.com.au

Approximate Coverage

4.9-9.8 m²/Litre after dilution

Shelf Life

E-CON™ containers are to be kept tightly sealed and stored in a cool, dry place. Shelf life is one year when stored properly, between 4 - 41°C. Keep from freezing.

Limitations

- Not to use as a curing compound
- Immediately wipe up any wet residue from hardened concrete surfaces

Cautions

- Avoid contact with skin, eyes and clothing
- Wash thoroughly after handling
- Do not take internally
- Wear skin and eye protection
- Please refer to Safety Data Sheet (SDS) before using
- Do not allow to freeze

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to colour, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

TECHNICAL DATA**Applicable Standard**

ACI-305R ACI-306

Note: For ASTM-C309 membrane compliance, see other LATICRETE® curing compounds and cure/sealers.

Physical and Working Properties

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE Australia. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

INSTALLATION**Mixing**

Shake or mix concentrate before dilution. Add 10 parts clean potable water to 1 part E-CON concentrate. Mix or shake again until thoroughly blended.

Application

Apply uniformly over fresh concrete using clean spray equipment with a fogging tip. Spray immediately after bull floating and during finishing operation as needed. The pink colour of E-CON can be used as a visual placement aid that will quickly dissipate and not discolour concrete. In extreme drying conditions, re-apply additional E-CON as needed. Use on fresh plastic concrete as well as between shake-on hardener applications. Apply lightly on hard to trowel floor areas. Do not puddle. Immediately wipe up any wet residue from hardened concrete surfaces.

Clean Up

Clean tools using soap and water.

AVAILABILITY AND COST**Availability**

LATICRETE® and materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

Non-finish LATICRETE® and LATAPOXY® installation materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

Periodic light applications are recommended to maintain gloss and protection.

TECHNICAL SERVICES**Technical assistance**

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE® is not responsible for any loss or damage arising from the incorrect use of this product.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

LATICRETE Australia Pty Ltd
29 Telford Street, Virginia
QLD 4014 Australia
1800 331 012
www.laticrete.com.au