



**Globally Proven
Construction Solutions**

SPARTACOTE™ METALLIC PIGMENT™

SPARTACOTE™ METALLIC PIGMENTS™ are composed of specialised aluminum prism pigments which are available in a powder form. These pigments are dispersed into SPARTACOTE FLEX SB™ polyaspartic coatings to create a remarkably iridescent effects with extraordinary colour variety and depth. These flooring systems provide architects and designers with the ability to create customised decorative flooring finishes with the enhanced durability necessary for heavy traffic environments.



FEATURES/BENEFITS

- Customisable finishes
- 12 Colours
- 3 coat process
- Low maintenance
- High reflectivity
- Suitable for any environment
- Provides incredible depth and radiance

APPROXIMATE COVERAGE

- 227 g / 3.8 Litres yields 2.4m² / Litre

MANUFACTURER

LATICRETE Australia Pty Ltd
29 Telford Street
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599
Toll Free: 1800 331 012
Fax: 07 3865 2250
Internet: www.laticrete.com.au

USES

- Decorative flooring for retail stores
- Car dealerships
- Residential flooring
- Stadium Flooring

PACKAGING

- 227 g (8 oz) Jar
- 908 g (32 oz) Jar

SHELF LIFE

- One Year Unopened

Cautions

FOR PROFESSIONAL USE ONLY

- Thoroughly read all technical data sheets, application guidelines, warranty disclaimers and Safety Data Sheets (SDS) prior to use. Application guides depending on the dye system employed are available at www.laticrete.com.au
- Polyaspartic aliphatic polyurea products contain chemical ingredients that are considered hazardous. Read the container label warning and SDS prior to use.
- Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes, if symptoms persist seek medical attention.

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to colour, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

TECHNICAL DATA

Working Properties

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE Australia. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

INSTALLATION

Please consult the SPARTACOTE™ System Application Guide.

AVAILABILITY AND COST

Availability

LATICRETE® and SPARTACOTE materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 1420 "SPARTACOTE Floor Maintenance Guide" available at www.laticrete.com for more information.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE is not responsible for any loss or damage arising from the incorrect use of this product.

LATICRETE Australia Pty Ltd

29 Telford Street, Virginia
QLD 4014 Australia

1800 331 012

www.laticrete.com.au