



SPARTACOTE™ Blended Chip

SPARTACOTE™ utilizes decorative vinyl colour chips, which are specially blended for SPARTACOTE Blended Chip and SPARTACOTE Blended Chip PURE, seamless, resin-based chip flooring systems. This unique product is random in shape, sized within a standardized range and custom blended to match any décor. Designed to increase durability and longevity while offering a high quality finish, our chips continue to gain popularity amongst architects, designers, contractors and consumers. They allow for customisation to commercial, residential and industrial floors with an endless range colour-styles, texture, size and blending options.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Available in standard vinyl as well as mica
- Good flexibility and strength
- Renewable and sanitary
- Easy to install
- Non-flammable
- Fully compatible with polyaspartic resins
- May be used to help hide small substrate imperfections

APPROXIMATE COVERAGE

- Standard Chip: 37.2 m²/25 kg box
- Mica Chip: 18.6 m²/25 kg box

SUITABLE SUBSTRATES

- Refer to specific SPARTACOTE Coating Data Sheet

MANUFACTURER

LATICRETE Australia Pty Ltd
29 Telford Street
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599
Toll Free: 1800 331 012
Fax: 07 3865 2250
Internet: www.laticrete.com.au

PACKAGING

- Standard Chip: 25 kg (55 lb) box
- Mica Chip: 11.3 kg (25 lb) box

SHELF LIFE

Unlimited. Store at 4° - 24°C in a covered area (out of the sun). Take special care into ensuring that chip is not exposed to moisture.

Limitations

- Keep SPARTACOTE Blended Chip out of the sun and at ambient temperature during use. Follow temperature guidelines for specific SPARTACOTE Coating being used.
- SPARTACOTE Blended Chip may fade or shrink if exposed to excess sunlight or high temperatures.
- Please note that with all resinous coating systems, exterior full sun environments in warm climates may exhibit above average surface temperatures. This is especially true with darker finishes. As a result, resinous systems may not be ideally suited for exterior pool deck applications.

Cautions

FOR PROFESSIONAL USE ONLY

- Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

TECHNICAL DATA

Applicable Standards and Test Methods

Working and Physical Properties

Size	3.2 - 6.4 mm
Thickness	127 micron DFT

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE Australia. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

INSTALLATION

Please consult the SPARTACOTE system Application Guide for SPARTACOTE Chip and SPARTACOTE Chip PURE system prior to use.

Broadcast:

SPARTACOTE Blended Chip or SPARTACOTE Mica Chip is to be broadcast by hand directly into consistently applied wet resin. Product should be left alone until underlying broadcast coat is completely dry.

AVAILABILITY AND COST

Availability

LATICRETE® and SPARTACOTE™ materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 1420 "SPARTACOTE Floor Maintenance Guide" available at www.laticrete.com.au for more information.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE is not responsible for any loss or damage arising from the incorrect use of this product.

LATICRETE Australia Pty Ltd

29 Telford Street, Virginia

QLD 4014 Australia

1800 331 012

www.laticrete.com.au