



# SPARTACOTE™ DIAMOND TOPP™

SPARTACOTE™ DIAMOND-TOPP™ is a high performance top-coat additive developed for heavy-duty environments requiring maximum abrasion resistance. The system consists of properly combining SPARTACOTE DIAMOND TOPP additive (a powder) directly with SPARTACOTE FLEX SB™.

**Globally Proven  
Construction Solutions**



## FEATURES/BENEFITS

- Textured, more non-slip surface
- Matte finish
- Stain resistant
- Maintenance-friendly
- May be incorporated as a top-coat over SPARTACOTE, urethane, or epoxy based resinous flooring systems.
- Improves wearability
- Easy to install
- Non-flammable
- Fully compatible with polyaspartic resins

## USES

- Heavy duty traffic areas
- Industrial floor coatings
- Environments requiring a textured matte finish

## PACKAGING

- 1.4 kg (3 lbs) jar
- 22.7 kg (50 lbs) bag

## MANUFACTURER

LATICRETE Australia Pty Ltd  
29 Telford Street  
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599  
Toll Free: 1800 331 012  
Fax: 07 3865 2250  
Internet: [www.laticrete.com.au](http://www.laticrete.com.au)

## COLOUR

Raw — White  
Dispersed In Coatings — Matte

## SUITABLE SUBSTRATES

- Refer to specific SPARTACOTE Coating Data Sheet

## Approximate Coverage

Load factor when added to SPARTACOTE™ FLEX™ Polyaspartic Top Coats. 0.9 kg per 3.8L

## Shelf Life

Unlimited. Store at 4° to 24°C in a covered area (out of the sun). Take special care into ensuring that the SPARTACOTE DIAMOND TOPP™ is not exposed to moisture.

## Limitations

Cannot be used with SPARTACOTE FLEX XT

## Cautions

Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to colour, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

## TECHNICAL DATA

### Applicable Standards and Test Methods

### Physical and Working Properties

Make Up	Fused Aluminum Oxide
Size	220-Mesh
Microns	165-170
Load Factor	1.4 kg per 3.8 Litres
Hardness (D2240)	94

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE Australia. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

## INSTALLATION

The material works best when dispersed into SPARTACOTE™ FLEX SB™ Low Gloss or SPARTACOTE™ FLEX SB™ pigmented polyaspartic during the mixing phase. The coating may then be applied as a top-coat over any SPARTACOTE or Epoxy based coating system. Once dry, SPARTACOTE™ DIAMOND TOPP™ will leave a lightly textured matte finish, suitable for heavy traffic environments.

## AVAILABILITY AND COST

### Availability

LATICRETE® and SPARTACOTE™ materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at [www.laticrete.com.au](http://www.laticrete.com.au)

### Cost

Contact a LATICRETE Distributor in your area.

## MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 1420 "SPARTACOTE Floor Maintenance Guide" available at [www.laticrete.com.au](http://www.laticrete.com.au) for more information.

## TECHNICAL SERVICES

### Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

### Technical and safety literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com.au](http://www.laticrete.com.au)

## DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE is not responsible for any loss or damage arising from the incorrect use of this product.

## LATICRETE Australia Pty Ltd

29 Telford Street, Virginia  
QLD 4014 Australia

1800 331 012

[www.laticrete.com.au](http://www.laticrete.com.au)