



TC50

TC50 is an acidic cleaner which may be used for a variety of purposes depending on the dilution. Its blend of acids and powerful detergents provides fast, effective removal of cement haze, dirt and building debris from ceramic tiled floors. TC50 is safe to handle when used according to directions. TC50 is colour coded orange for easy identification. TC50 is a commercial strength cleaner.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Clear orange mobile liquid with mild odour
- Concentrated for economy
- Fast acting
- Multipurpose
- Effective on a variety of soils
- Kills bacteria and provides a hygienic clean surface
- Free rinsing
- Biodegradable to AS1792-1976
- Australian made

PACKAGING/COLOUR

- 1 litre bottle; 12 bottles per carton
- 5 litre jug; 3 jugs per carton

MANUFACTURER

LATICRETE Australia Pty Ltd
29 Telford Street
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599
Toll Free: 1800 331 012
Fax: 07 3865 2250
Internet: www.laticrete.com.au

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) year if stored correctly.

Cautions

- TC50 is acidic, use appropriate gloves, eye protection and protective clothing. See MSDS for more information.
- Avoid inhaling, provide adequate ventilation.
- TC50 is not intended for everyday use.
- Do not use on marble.
- Do not use with other chemicals or cleaners.
- Close container after each use.
- Store in original container.
- Do not take internally.
- Keep out of reach of children.

Note: The instructions are a condensed guide and should not be considered to be complete.

APPLICATION

Grout and tile installation systems should be allowed to cure prior to application. Test in an inconspicuous area with a 24 hour time lapse prior to extended use. Surface temperature should be between 7°C to 30°C. Pre wet surface to be treated with clean water and allow penetrating. After surface is hydrated, remove any free standing water to begin cleaning with TC50. For grout haze on tiled floor, dilute the TC50 1:1 with clean water and mop over area liberally and allow to dwell for 1 to 2 minutes. Scrub with white nylon scrub pad as required and do not allow to dry on surface. Rinse off with plenty of clean water whilst scrubbing down to ensure complete removal of cleaner.

AVAILABILITY AND COST

Availability

LATICRETE and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at

www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and liability is assumed by the user when used incorrectly and not in accordance with LATICRETE guidelines.
- The manufacturer is not responsible for any loss or damage arising from incorrect usage of this product.
- The specifier or other party responsible for the project must ensure that the details in this data sheet are appropriate for the intended application and that additional detailing is performed for specific design or any areas that fall outside the scope of this specification.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty. The use of LATAPOXY 310 Stone Adhesive, LATAPOXY 300 Adhesive, SPECTRALOCK® PRO Premium Grout[†], LATAPOXY SP-100 and SPECTRALOCK 2000 IG will not contribute to any noticeable efflorescence.

LATICRETE Australia Pty Ltd

29 Telford Street, Virginia

QLD 4014 Australia

1800 331 012

www.laticrete.com.au

[†] United States Patent No.: 6,881,768 (and other Patents).