



Globally Proven
Construction Solutions

4237 Latex Additive



FEATURES

- Superior bond strength
- Flexible and shock resistant
- Weather and frost resistant for interior and exterior use in all types of climates
- Safe, economical and easy to use; non-hazardous, non-flammable
- Can be mixed with PERMACOLOR® Grout

BENEFITS

- Secures tile and stone under the harshest conditions.
- Ideal for extra heavy traffic conditions.
- Perfect for extreme freeze/thaw conditions.
- No harmful fumes. Great for areas where odour or harsh chemicals would be dangerous.
- Great where coloured adhesives are required.

Uses

- Used for installation of all types of ceramic tile, brick, natural stone and agglomerates
- Water resistance makes it acceptable for submerged applications

Suitable Substrates

- Concrete
- Brick masonry
- Concrete masonry
- Cement mortar beds
- Gypsum wallboard†
- Cement terrazzo
- Cement plaster
- Cement backer board*
- Ceramic tile and stone

Packaging

19 litre pail; 32 pails per pallet

Approximate Coverage Per 19 litre Pail[^]

[^]When mixed with 75 kg of 211 Crete Filler Powder

6 mm x 6 mm notched trowel	25 – 30 m ²
6 mm x 9 mm notched trowel	18 – 23 m ²

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au



Snap for information.

* Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use. † Interior only.