



Globally Proven  
Construction Solutions

# ULTRA X8

For installing porcelain, vitrified, ceramic and stone tile to floors and walls in both internal and external areas.



Product Data Sheet 1038



## FEATURES

- Good balance of performance and coverage
- Fibre reinforced for better workability
- Smooth and creamy consistency
- Meets and exceeds AS ISO 13007 as a C1TES1
- Strong bond

## BENEFITS

- An economical performer.
- Non-sag and non-shrink performance.
- Easy to spread and apply.
- Performance proven to meet all applicable standards.
- Suitable for a wide range of internal and external substrates.

## Uses

- Designed for interior and exterior floor and wall installations
- Use over LATICRETE Waterproof Membranes

## Suitable Substrates

- Concrete
- Concrete masonry
- Cement mortar beds
- Ceramic tile and stones<sup>^</sup>
- Suitable waterproof membranes
- Brick masonry
- Cement terrazzo<sup>^</sup>
- Gypsum wall board<sup>^</sup>
- Cement backer board<sup>\*\*</sup>

## Packaging

20 kg bag; 56 bags per pallet

## Available Colour

White

## Approximate Coverage Per Bag

6 mm x 6 mm notched trowel	7 – 8 m <sup>2</sup>
6 mm x 9 mm notched trowel	4.5 – 5 m <sup>2</sup>

(Based on product wet densities with a trowel at 45°)  
(Coverage will depend on how the trowel is used and surface regularity.)

For the latest information on the features and use of this product, consult the product Data Sheet on our website at [www.laticrete.com.au](http://www.laticrete.com.au)



Snap for information.

<sup>^</sup> Interior use only  
<sup>\*\*</sup> Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.