



STONETECH® Epoxy Grout Haze & Coating Stripper

STONETECH Epoxy Grout Haze & Coating Stripper is a fast-acting, water-based gel designed to safely remove tough epoxy grout haze and various coatings from vertical and horizontal surfaces.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Eliminates epoxy grout haze in 10 minutes or less
- Safely removes epoxy grout haze and tough coatings - varnish, lacquer, sealer, wax, paint, polyurethane and acrylic
- Water-based formula
- Fast-acting gel – great for vertical and horizontal applications
- Low odour and non-flammable
- Professional strength
- No Methylene Chloride

USES (INTERIOR & EXTERIOR)

- Countertops
- Backsplashes
- Floors
- Walls

PACKAGING

- Sample 59 ml, 12 units per Case
- 946 ml, 6 units per Case
- 3.8 L, 4 units per Case

RECOMMENDED SURFACES

Natural stone, masonry, tile and grout, such as:

- | | |
|--------------|------------------|
| ▪ Granite | ▪ Flagstone |
| ▪ Marble | ▪ Quartzite |
| ▪ Limestone | ▪ Concrete |
| ▪ Bluestone | ▪ Saltillo Tile |
| ▪ Travertine | ▪ Quarry tile |
| ▪ Sandstone | ▪ Ceramic tile |
| ▪ Slate | ▪ Porcelain tile |

MANUFACTURER

LATICRETE Australia Pty Ltd
29 Telford Street
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599
Toll Free: 1800 331 012
Fax: 07 3865 2250
Internet: www.laticrete.com.au

Approximate Coverage

- 8.2 m²/946 ml for a single coat application
- 32.5 m²/3.8 L for a single coat application

Coverage is dependent on the age of the coating, type of film and its thickness.

VOC Content

11.4% US (Consumer Products)

Cautions

- Consult SDS for more safety information.
- Skin contact: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage and Handling Instructions

WARNING: CAUSES SERIOUS EYE DAMAGE. CAUSES SKIN IRRITATION. Avoid contact with eyes and skin. Use protective eyewear and gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 38°C. Do not mix with other chemicals. Do not flush unused product to natural waterways or sanitary sewer system. Dispose of in accordance with waste disposal regulations.

TECHNICAL DATA

Physical Properties

Form	Gel
Colour	off-white to light green
Odour	Citric
pH	4

INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Test in a small inconspicuous area to determine ease of application and desired results. Be sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Ensure work area is well ventilated during application and until surface is dry. Keep children and pets out of the area until surface use resumes. Avoid contact with surfaces not intended to be treated. Avoid applying in direct sunlight. Should not be used in extreme temperatures. Recommended application temperature range is 10°C to 32°C.

Directions

- SHAKE WELL BEFORE USING. Do not dilute before applying.
- Liberally apply an even coat of STONETECH® Epoxy Grout Haze & Coating Stripper over the area with a paint brush, mop or paint pad. DO NOT APPLY WITH A SPRAYER. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
- Let STONETECH® Epoxy Grout Haze & Coating Stripper dwell as follows:

Haze / Coating	Surface Type	Age of Haze/Coating		
		24hr	7 days	>7 days
Epoxy Grout Haze	Tile	1–3 min	3–5 min	10 min
Epoxy Grout Haze	Natural Stone & Masonry	1–3 min	5–10 min	10 min
Coatings*	Tile	1–5 min		
Coatings*	Natural Stone & Masonry	1–5 min		10 min

Application time may vary depending on the surface texture, and age /thickness of haze.

*Coatings such as varnish, lacquer, sealer, wax, paint, polyurethane, acrylic and stain.

- Do not let product dry on the surface. If it starts to dry, add more to keep surface wet.
- Agitate surface with a nylon scrub brush or pad after testing a small area first to make sure that brush or pad will not scratch stone. Surface can be wet with water to enable easier removal of epoxy grout haze or coating
- Wipe up residual with clean, dry cloth or wet mop. A wet/dry vacuum can be used for larger area.
- Rinse surface well with clean water.
- More than one application may be required, repeat steps 1 through 7 when necessary.
- Surface traffic may begin after 2 hours or when surface is dry.

AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the STONETECH sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 1262 Stone and Tile Care Guide.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at

www.laticrete.com.au

DISCLAIMER

The information contained in this document is given in good faith and to the best of our knowledge is true and accurate. This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information. The use of this product is beyond our control and LATICRETE® is not responsible for any loss or damage arising from the incorrect use of this product. Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

LATICRETE Australia Pty Ltd

29 Telford Street, Virginia

QLD 4014 Australia

1800 331 012

www.laticrete.com.au