



Globally Proven
Construction Solutions

PERMACOLOR® NS Grout



FEATURES

- Consistent colour
- Contains anti-microbial technology
- 1 step – mix with water
- Stain-resistant
- Easy application and clean-up

BENEFITS

- No blotchiness, resists efflorescence (compared to other Portland cement-based grout)
- Inhibits the growth of stain-causing mould and mildew growth in the grout joints
- Easy to install, no additive required
- Easy to clean, dense and non-shrinking, highly stain-resistant for a cement-based grout
- Faster to install and finish, no damp curing required

Uses

- Ceramic tile and stone applications
- Interior and exterior
- Floors and walls
- Excellent for dry and wet areas

Suitable Substrates

- Marble
- Porcelain tile
- Granite
- Quarry tile
- Ceramic tile
- Glass mosaic
- Stone

Packaging

5 kg bag; 4 bags per carton

Available Colours

12 lifestyle colours in 5 kg bags
(please refer to colour chart)

Approximate Coverage Per 5 kg Bag – m²

Tile Size	Joint Width		
	1.5 mm	3 mm	6 mm
25 x 25 x 6 mm	4.3	2.3	1.4
50 x 50 x 6 mm	8.3	4.3	2.3
100 x 100 x 8 mm	12.2	6.2	3.2
150 x 150 x 9 mm	16.1	8.2	4.2
200 x 200 x 9 mm	21.4	10.8	5.5
300 x 300 x 9 mm	32.0	16.1	8.2
325 x 325 x 9 mm	34.6	17.4	8.8
400 x 400 x 9 mm	42.6	21.4	10.8
425 x 425 x 9 mm	45.2	22.7	11.5
600 x 600 x 9 mm	63.7	32.0	16.1

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au

Certain types of stone and tile are more absorbent than others and will trap colour pigment during grouting. Prior to grouting, test for absorption of colour pigment. Porous tiles will need to be sealed prior to grouting, this includes polished porcelain. Use caution when polishing soft glazed tiles or polished stone.

Snap for information.

