



Globally Proven
Construction Solutions

125 TRI MAX™

Three products in one thin-set with maximum performance



Product Data Sheet 1255



FEATURES	BENEFITS
Anti-fracture and sound protection in one step	Install tile fast reducing labor and material cost
Single component – just add water	Easy to mix, spread and use
Lightweight	22.7 kg coverage in a 11.4 kg bag
36% post consumer recycled content	Contributes to LEED
Reinforced with Kevlar®	A stronger installation
Extra Heavy per ASTM C627 Robinson Floor Test – TCNA	Can be used in high traffic areas

Suitable Substrates

- Concrete
- Cement mortar beds
- Cement backer board†
- Ceramic tile and stone
- Exterior glue plywood
- Brick masonry
- Cement terrazzo
- Poured gypsum underlayments

† Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for use.

Packaging

11.4 kg bag. 56 bags per pallet.

Uses / Advantages

- Replace sheet or liquid membrane and thin-set combinations for crack isolation and sound control with one product saving time, labor and money
- Add to the sound deadening for the floor construction with a Delta IIC of 16
- Prevent the transmission of non-structural cracks up to 3 mm
- Thin-bed or medium-bed applications
- Can be used with any size tile or stone

Available Colour

Grey

