



Globally Proven
Construction Solutions

HYDRO BAN[®] SLURRY

HYDRO BAN SLURRY is a cement based, one component, polymer fortified, waterproof material that mixes with water and easily applies with brush, roller or trowel.



Product Data Sheet 1259



FEATURES	BENEFITS
Resists negative hydrostatic pressure.	Resists up to 2.5 BARS of negative hydrostatic pressure on retaining walls, in basements and cement slabs on-ground.
“Extra Heavy Service” rating	Per TCNA performance levels (RE: ASTM C627 Robinson Floor Test).
Rapid drying	Faster time to tile.
Easily applied with roller, brush.	Easy to apply, no special techniques involved.
Supports direct adhesion.	Install tile, brick and stone directly onto the membrane.
Part of the HYDRO BAN waterproofing system	Can be used under HYDRO BAN in swimming pools where negative hydrostatic pressure resistance is required.
Bonds directly to metal, PVC and ABS plumbing fixtures.	No need to use multiple materials around pipe penetrations or drains.

Suitable Substrates

- Concrete
- Concrete & Brick Masonry
- Cement Mortar Beds
- Cement Plaster
- Ceramic Tile & Stone*
- Cement Terrazzo*
- Cement Backer Board**

* If skim coated with a Latex Thin-Set Mortar.

**Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.

Uses / Advantages

- Interior and exterior.
- Garden fountains and water features.
- Retaining walls and basements.
- Driveways and landscaped works.
- Where substrate moisture is problematic.

Available Colour

Grey

