



Globally Proven
Construction Solutions

LEVEL

LEVEL is a cement-based underlayment for use in levelling interior substrates. LEVEL produces a flat, smooth and hard surface for the installation of finished flooring. LEVEL can be placed from 3mm – 76mm in a single lift.



Product Data Sheet 1234



FEATURES	BENEFITS
Multi-purpose	Can be used on a wide range of substrates.
Rapid drying	Walkable in 2–3 hours after pouring @21°C
Fast installation	Pourable and pumpable
Economical	Can be poured from 3mm to 76mm
Versatile	Suitable surface for most finished floor goods
Inorganic	Will not contribute to mould/mildew growth

Suitable Substrates

- Concrete
- Vinyl Tile
- Cement Terrazzo
- Exterior Glue Plywood
- Ceramic Tile and Stone
- Cement Mortar Beds
- Cement Backer Board*

* Consult cement backer board manufacturer for specific installation recommendations.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for one (1) year* if stored off the ground in a dry area.

* High humidity will reduce the shelf life of bagged product.

Coverage

Per 20 kg bag

Nominal Thickness	Approximate Coverage
3mm	3.9m ²
5mm	2.34m ²
10mm	1.17m ²
25mm	0.47m ²
50mm	0.23m ²
76mm	0.15m ²

Packaging

20Kg bags, 56 per pallet

