



COLORED QUARTZ

COLORED QUARTZ is a variety of blends consisting of colour particle and mineral type raw materials, which are mixed together for the decorative finishing of floors, available in eight blends. Ideal for Ant-skid floors where water molecules on footwear could cause sliding and residue on the floor surface.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Highly Decorative Solution
- Anti-Slip Rating comparable to R12
- Interior & Exterior use
- Non-Toxic, very low VOC
- Easy to Apply

USES

- Interior and exterior
- Floors
- Increased traction

MANUFACTURER

LATICRETE EUROPE S.R.L .

Via Viazza 1° Tronco nr 19

41043 Formigine (MO) – Italy

Ph. +39 059557680

info@laticreteurope.com

STANDARDS/CERTIFICATIONS

Meets Émissions dans L'air Intérieur France



Suitable Substrates

As per Polyaspartic Coating

Packaging

- 10 Kg box

Approximate Coverage

Single Broadcast: 200 ft² (18.8 m²) / 50 lb bag

Double Broadcast: 100 ft² (9.4 m²) / 50 lb bag

Shelf Life

Unlimited. Store at 4°-24°C in a covered area (out of the sun). Take special care into ensuring that quartz is not exposed to moisture.

Color

Eight Blends

Limitations

Refer to data sheet for applicable Polyaspartic Coatings

Cautions

- Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

TECHNICAL DATA**Sieve Specification On Solid Colours**

Fraction (Mm)	Percentage (%)
0,00-0,125	0 - 1 %
0,125-0,25	25 - 35 %
0,25-0,50	55 - 70 %
0,50-1,00	6 - 12 %
1,00-1,40	0 - 1 %
>1,4	0%

Properties

Specific Weight : 2,3 – 2,5 G/Cm³

Formaldehyde : < 10 Ppm

Voc: < 1 G/L

Solid Content: 100%

Flexibility: High

Light-Fastness: Low

INSTALLATION

COLORED QUARTZ is to be broadcast by hand directly into consistently applied wet resin. Product should be left alone until underlying broadcast coat is completely dry.

APPLICATION

COLORED QUARTZ can be applied by full broadcast and by Hopper Spray if required. It is advisable to use a similar colour pigment primer to the blend required.

After use, brush off excess blended quartz and finish with transparent top coat. Ensure that the surface is kept free of any contaminants (dirty footwear, tools etc) until the resin has cured.

AVAILABILITY AND COST**Availability**

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l. Telephone +39 059557680. For on-line distributor information, visit www.laticrete.eu

Cost

Contact a LATICRETE® closer distributor to obtain complete information and cost.

WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year.

Contact Technical Support for further information

MAINTENANCE

LATICRETE® products are of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

TECHNICAL SERVICES

Technical assistance

For information contact: +39 059557680

info@laticreteurope.com

Technical and safety literature

To obtain technical and safety literature, please visit our website at www.laticrete.eu

Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® unable to directly control the installation conditions and modalities of application of products, do not assume any liability arising from their implementation. Those who want to use the LATICRETE® products must conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.