



**Globally Proven  
Construction Solutions**

# METALLIC PIGMENTS

METALLIC PIGMENTS are composed of specialized aluminum prism pigments which are available in a powder form. These pigments are dispersed into GUARD PA SB polyaspartic coatings to create a remarkably iridescent effects with extraordinary color variety and depth. These flooring systems provide architects and designers with the ability to create customized decorative flooring finishes with the enhanced durability necessary for heavy traffic environments.



## FEATURES/BENEFITS

- Customizable finishes
- 12 Colors
- 3 coat process
- Low maintenance
- High reflectivity
- Suitable for any environment
- Provides incredible depth and radiance

## USES

- Decorative flooring for retail stores
- Car dealerships
- Residential flooring
- Stadium Flooring

## MANUFACTURER

LATICRETE EUROPE S.R.L .

Via Viazza 1° Tronco nr 19

41043 Formigine (MO) – Italy

Ph. +39 059557680

info@laticreteurope.com

## STANDARDS/CERTIFICATIONS

**Packaging**

227 g Jar  
908 g Jar

**Approximate Coverage**

227 g/ 3.8 L, 2.4 m<sup>2</sup>/L

**Shelf Life**

One year unopened

**Cautions****FOR PROFESSIONAL USE ONLY**

- Thoroughly read all technical data sheets, application guidelines, warranty disclaimers and Safety Data Sheets (SDS) prior to use. Application guides depending on the dye system employed are available at [www.laticrete.com](http://www.laticrete.com).
- Polyaspartic aliphatic polyurea products contain chemical ingredients that are considered hazardous. Read the container label warning and SDS prior to use.
- Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 Minutes, if symptoms persist seek medical attention.

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

**TECHNICAL DATA****Applicable Standards and Test Methods****Physical and Working Properties**

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not be construed as a warranty or guaranty of any kind.

Satisfactory results depend upon many factors beyond the control of LATICRETE International, Inc. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

**INSTALLATION**

Please consult the Resinous Flooring System Application Guide.

**AVAILABILITY AND COST****Availability**

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l. Telephone +39 059557680. For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu)

**Cost**

Contact a LATICRETE® closer distributor to obtain complete information and cost.

**WARRANTY**

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year.

Contact Technical Support for further information

**MAINTENANCE**

LATICRETE® products are of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

**TECHNICAL SERVICES****Technical assistance**

For information contact: +39 059557680

[info@laticreteurope.com](mailto:info@laticreteurope.com)

**Technical and safety literature**

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu)

**Warning**

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® unable to directly control the installation conditions and modalities of application of products, do not assume any liability arising from their implementation. Those who want to use the LATICRETE® products must conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.