



# STONETECH® KLENZALL™ CLEANER

DS-2150-1220

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® KLENZALL™ CLEANER

## 2. MANUFACTURER

LATICRETE EUROPE S.r.l.

Via Paletti, 1, 41051

Castelnuovo Rangone MO, Italy

Telephone: +39 059557680

Email: [info@laticreteurope.com](mailto:info@laticreteurope.com)

Website: [laticrete.eu](http://laticrete.eu)

## 3. PRODUCT DESCRIPTION

STONETECH® KLENZALL™ CLEANER is the heavy duty strength, alkaline cleaner made to remove the toughest dirt, grease and grime from natural stone, tile, masonry and grout. It cleans, degreases and prepares the surface for resealing, is safe on stone and is low VOC.

STONETECH® KLENZALL™ CLEANER can be used for frequent and deep cleaning with different dilution ratios, good for use on heavily used areas such as countertops, walls or floors.

### Uses

- Countertops
- Backsplashes
- Floors
- Walls

### Advantages

- For natural stone, tile, masonry and grout

- Removes tough dirt, grease and grime
- Cleans, degreases and prepares surface for resealing
- Safe on stone, will not etch
- Water-based, alkaline formula
- Can be used pure for deep cleaning or diluted for frequent cleaning

### Suitable Substrates

- Natural Stone
- Granite
- Marble
- Quarry Tile
- Ceramic Tile
- Porcelain tile
- Grout
- Masonry

### Packaging

1 lt x 12/box

5 lt x 4/box

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).>

### Cautions

Consult SDS for more safety information.

- Wear eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention immediately.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

**Storage and Handling Instructions:** CORROSIVE. HARMFUL IF SWALLOWED. MAY CAUSE SEVERE EYE AND SKIN BURNS, AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Use protective eyewear and gloves. Avoid prolonged exposure to vapors. Use in a well-ventilated

area. For repeated or professional spray use, a respirator is recommended. Consult SDS. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100 °F (38 °C). Do not mix with other chemicals. Do not release to natural waterways.

#### 4. TECHNICAL DATA



#### Physical Properties

Form:	Liquid
Colour:	Colourless/Amber
pH:	12
VOC Content:	31 g/lit

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### 5. INSTALLATION

Read entire label before using. Use only as directed. Be sure surfaces to be cleaned are swept or vacuumed to remove loose debris. Avoid skin and eye contact with product. Wear protective eyewear and gloves when handling. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

1. Prior to using, test on a discrete area or scrap piece of tile to insure desired results.
2. Shake well before use.
3. Use pure or diluted with water:

Use	STONETECH® KLENZALL™ CLEANER	Water	Ratio
Frequent Cleaning	100 - 300 ml	10 L	1:100 to 3:100
Deep Cleaning	1 L	4-10 L	1:4 to 1:10
Heavy Duty / Wax Remover	Pure	--	--

4. Apply mixed solution with a mop, clean cloth, brush, or appropriate professional cleaning equipment (i.e. medium-hard single disc floor cleaner).
5. Lightly rub with a scrub brush or floor machine as needed.
6. Remove STONETECH® KLENZALL™ CLEANER residues using a clean cloth, wet/dry vacuum, or damp mop.
7. Rinse area well with clean water.
8. Let area dry completely before using. Reseal cleaned area with a STONETECH sealer.

#### 6. AVAILABILITY AND COST

##### Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l.:

+39 059557680

[info@laticreteurope.com](mailto:info@laticreteurope.com)

For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu).

##### Cost

Contact LATICRETE EUROPE S.r.l to obtain complete information and cost.

#### 7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical Services for further information. See 10. FILING SYSTEM:

- DS230.13EU: 1 Year Product Warranty (EN)

#### 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® STONE & TILE CLEANER is recommended.

For tough or difficult to remove soil use STONETECH® KLENZALL™ CLEANER, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

#### 9. TECHNICAL SERVICES

##### Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059557680

[technicalservices@laticreteurope.com](mailto:technicalservices@laticreteurope.com)

##### Technical and Safety Literature

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu).

##### Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from

their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.