



STONETECH® BULLETPROOF® SEALER

DS-2820-0121

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® BULLETPROOF® SEALER

2. MANUFACTURER

LATICRETE Europe S.r.l. a socio unico

Via Paletti, snc, 41051

Castelnuovo Rangone MO, Italy

Telephone: +39 059 535540

Email: info@laticreteurope.com

Website: laticrete.eu

3. PRODUCT DESCRIPTION

STONETECH BULLETPROOF® SEALER is the premium, water-based penetrating sealer, designed to provide maximum stain protection against the toughest oil and water-based stains.

This professional grade sealer effectively impregnates into the most porous natural stone, tile, masonry and grout surfaces in interior and exterior applications and does not alter the natural look of the surface. A high performing, safer alternative to solvent based sealers, STONETECH BULLETPROOF SEALER is better for you and the environment.

Uses

- For interior and exterior use
- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Offers maximum stain protection
- Best protection for the most porous natural stone, tile, masonry and grout
- Preserves the original look of the surface
- Water-based formula is better for you and the environment
- Professional grade

Suitable Substrates

- Granite
- Marble
- Quartzite
- Travertine
- Sandstone
- Saltillo
- Bluestone
- Flagstone
- Grout

Packaging

- 1 lt x 12/box
- 5 lt x 4/box

Coverage / Consumption

~8-12 m² / 1 liter

Consumption will vary depending on porosity and absorption of surface.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).>

Cautions

Consult SDS for more safety information.

Storage and Handling Instructions: Store only in the original container. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals.

4. TECHNICAL DATA



7. Should a sealer residue appear, rewet the impacted section of the surface with sealer. Agitate the surface with a white nylon scrubbing pad to loosen residue and wipe dry with a clean, absorbent towel.
8. A full cure is achieved in 24-72 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
9. Clean tools used during application with water

Expected Wear

- Up to 5 years on interior surfaces
 - Up to 3 years on exterior surfaces
- For best results, reapply annually.

Physical Properties

Form:	Liquid
Colour:	Clear / Slightly Yellow
Odour:	Alcohol
pH:	5
VOC Content:	0 g/lit

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24 hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application.

Make sure surface is clean and free of waxes and coatings. Surface temperature should be between 10°C and 26°C. Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

Directions

1. Ensure cap is closed and sealed, and shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally apply an even coat of STONETECH® BULLETPROOF SEALER using a paint pad, roller, or brush.
4. Allow sealer to penetrate the surface for 10-15 minutes. During this time, keep the surface wet with sealer, adding more sealer as needed. **DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.**
5. Thoroughly wipe dry the entire surface with clean absorbent towels.
6. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied within 30-40 minutes from the initial application as directed in steps 3-5.

6. AVAILABILITY AND COST

Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l.:

+39 059 535540

info@laticreteeuropa.com

For on-line distributor information, visit www.laticrete.eu.

Cost

Contact LATICRETE EUROPE S.r.l to obtain complete information and cost.

7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical Services for further information. See 10. FILING SYSTEM:

- DS230.13EU: 1 Year Product Warranty (EN)

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance.

Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® STONE & TILE CLEANER is recommended. For tough or difficult to remove soil use STONETECH KLENZALL™ CLEANER, a nylon scrubbing pad or a long handled stiff bristle brush.

Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059 535540

technicalservices@laticreteurope.com

Technical and Safety Literature

To obtain technical and safety literature, please visit our website at www.laticrete.eu.

Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.eu. The following is a list of related documents:

- DS 230.13EU: 1 Year Product Warranty
- DS 2110: STONETECH STONE & TILE CLEANER
- DS 2150: STONETECH KLENZALL™ CLEANER
- TDS 262: Stone and Tile Care Guide