

SPECTRALOCK® DAZZLE™

DS-6851-1221

Globally Proven Construction Solutions



1. PRODUCT NAME

SPECTRALOCK® DAZZLE™

2. MANUFACTURER

LATICRETE Europe S.r.l. a socio unico Via Paletti, snc, 41051

Castelnuovo Rangone MO, Italy
Telephone: +39 059 535540
Email: info@laticreteeurope.com

Website: laticrete.eu

3. PRODUCT DESCRIPTION

A unique design component, SPECTRALOCK® DAZZLE $^{\text{TM}}$ adds metallic and "Glow-In-The-Dark" enhancements to SPECTRALOCK® PRO PREMIUM GROUT. These high-end design elements offer limitless imaginative applications.

Use SPECTRALOCK DAZZLE on walls and floors. Add a metallic look to plain tile and stone. Accentuate metallic tiles, glass tiles, mosaics and stone with "dazzling" colour combinations and effects.

Use SPECTRALOCK DAZZLE in your pools and spas. Use Glow-in-the-Dark in your bathrooms, hallways and entryways.

Uses

- For use in interior and exterior applications on floors and walls
- Good for submerged use and wet applications

Suitable Substrates

Epoxy Grout

Packaging

Part D: 1 jar (195 g)

Available Finishes

- GOLD
- SILVER
- COPPER
- MOTHER OF PEARL
- GLOW IN THE DARK

Approximate Coverage / Consumption

Use four (4) Part D DAZZLE jars per full unit (5.2 kg kit) of SPECTRALOCK PRO PREMIUM GROUT.

Shelf Life

Unlimited. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun).

Limitations

 SPECTRALOCK DAZZLE™ (Glow) not for use in submerged installations.

Cautions

Refer to Safety Data Sheet (SDS) for details before use.

 SPECTRALOCK DAZZLE (Glow) might discolour from strong alkali cleaners and acids. Use a neutral pH solution of soap and water when cleaning SPECTRALOCK PRO PREMIUM GROUT mixed with SPECTRALOCK DAZZLE (Glow).

4. TECHNICAL DATA

Physical Properties

Refer to SPECTRALOCK® PRO PREMIUM GROUT product datasheet for physical and working properties.

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Refer to SPECTRALOCK® PRO PREMIUM GROUT product datasheet for mixing and installation instructions.

6. AVAILABILITY AND COST

Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE Europe S.r.l. a socio unico:

+39 059 535540 info@laticreteeurope.com

For on-line distributor information, visit www.laticrete.eu.

Cost

Contact LATICRETE Europe S.r.l. a socio unico to obtain complete information and cost.

7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical Services for further information. See 10. FILING SYSTEM:

• DS 230.13EU: 1 Year Product Warranty

8. MAINTENANCE

LATICRETE® and LATAPOXY® are products of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending on the cleaning products used.

LATICRETE recommends using STONETECH® surface products to protect, clean and enhance stone, masonry, tile and grout surfaces. Use STONETECH® EPOXY GROUT HAZE & COATING STRIPPER for epoxy film/haze that has cured on tile surface and is difficult to remove

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059 535540

technicalservices@laticreteeurope.com

Technical and Safety Literature

To obtain technical and safety literature, please visit our website at www.laticrete.eu.

Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field

performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

10. FILING SYSTEM

Additional product information is available on our website at <u>laticrete.eu</u>. The following is a list of related documents:

- DS230.13EU: 1 Year Product Warranty
- DS 65316: SPECTRALOCK® PRO PREMIUM GROUT Product Datasheet
- TDS 400: Grout Guide