



Printing date 28.05.2019 Revision: 28.05.2019

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: FAST-FIX Part. A
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Construction chemicals
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

LATICRETE EUROPE Srl

Bahnhofstraße 36, 4802 Ebensee AUSTRIA

Contact: D.Pilz: +43 660 900 6500 Mail: Info@laticreteaustria.com

www.laticrete.eu

Notruf Nummer: +49 / (0)70024112112(LER)

For shipment to USA

outside USA: +49 / (0)70024112112(LER); inside USA: +49 / (0)70024112112(contact ID: LER)

- · Further information obtainable from: Abteilung Produktsicherheit
- · Emergency telephone number: Während der normalen Öffnungszeiten: +49 / (0)700 24 11 21 12

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 1)

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

4,4'-methylenediphenyl diisocyanate

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 3)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues		
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335		
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate		
EINECS: 202-966-0	& Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;		
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	1–20%	
EINECS: 265-198-5	🗞 Asp. Tox. 1, H304		

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³

Sen; as -NCO

(Contd. on page 5)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 4)

101-68-8 4,4'-methylenediphenyl diisocyanate

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

Ingredients with biological limit values:

101-68-8 4,4'-methylenediphenyl diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Brown

Odour: Petrol-like

Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 190 °C

· Flash point: >204 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 400 °C

Decomposition temperature: Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapour pressure at 20 °C: 0 hPa

Density at 20 °C: 1.24 g/cm³

Not determined.

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 7)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content: VOC (EC)	0.00 %
Solids content: Other information	0.0 % No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc 2

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

(Contd. on page 8)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
HP 4	Irritant - skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 7	Carcinogenic	
HP 13	Sensitising	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· UN-Number	
· ADR, IMDG, IATA	UN2810
· UN proper shipping name	
· ADR	2810 TOXIC LIQUID, ORGANIC, N.O.S. (4,4'-
	methylenediphenyl diisocyanate,
	diphenylmethanediisocyanate,isomeres and
	homologues), ENVIRONMENTALLY HAZARDOUS
· IMDG, IATA	TOXIC LIQUID, ORGANIC, N.O.S. (4,4'-
	methylenediphenyl diisocyanate,

(Contd. on page 9)

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 8)

	(Conta. of page o
	diphenylmethanediisocyanate,isomeres and homologues)
· Transport hazard class(es)	
· ADR, IMDG, IATA	
6	
·Class	6.1 Toxic substances.
Label	6.1
· Packing group	
· ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Toxic substances.
· Danger code (Kemler):	60
· EMS Number:	F-A,S-A
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of and the IBC Code	of Marpol Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
. , ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (4,4'-METHYLENEDIPHENYL DIISOCYANATE, DIPHENYLMETHANEDIISOCYANATE,ISOMERES AND HOMOLOGUES), 6.1, 111, ENVIRONMENTALLY HAZARDOUS
	(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.05.2019 Revision: 28.05.2019

Trade name: FAST-FIX Part. A

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56a
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: Doris Pilz-
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1