

**GUARD PA PART B**  
**9115-0002B-2BA****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** GUARD PA PART B  
9115-0002B-2BA
- Other means of identification:**
- UFI:** 6C00-Y06S-900V-9MRA
- Product registration number:** 9115-0002B-2BA
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Two component high performance coating for metallic surfaces, wood, concrete, etc.... For professional users only.  
PROC7 Industrial spray applications  
PROC10 Application with rollers or brushes  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
LATICRETE EUROPE SRL  
Via Paletti Snc  
41051 Castelnuovo Rangone - ITALY  
Phone: 059535540  
info@laticreteeurope.com  
https://eu.laticrete.com/
- 1.4 Emergency telephone number:** Company number (08:00 - 18:00 CET): (+39) 059 557680 - European emergency number: 112

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:****CLP Regulation (EC) No 1272/2008:****Warning****Hazard statements:**

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof equipment.  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P405: Store locked up.  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH204: Contains isocyanates. May produce an allergic reaction.  
Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Mixture of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylolol.

**Additional Labelling (Annex XVII, REACH):**

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

**GUARD PA PART B**  
**9115-0002B-2BA**



**SECTION 2: HAZARDS IDENTIFICATION (continued)**

As from 24 August 2023 adequate training is required before industrial or professional use.

**Acute Toxicity Estimate (ATE mix):**

39,6 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

**UFI:** 6C00-Y06S-900V-9MRA

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of additives, pigments and resins

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17-XXXX	Hexamethylene diisocyanate, oligomers <sup>[1]</sup>	Self-classified	50 - <75 %
Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning		
CAS: 128601-23-0 EC: Non-applicable Index: Non-applicable REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics (Benzene < 1 % w/w) <sup>[1]</sup>	Self-classified	30 - <50 %
Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	   	
CAS: Non-applicable EC: 400-830-7 Index: 607-176-00-3 REACH: Non-applicable	Mixture of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylololyl <sup>[1]</sup>	Self-classified	0,1 - <1 %
Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	 	
CAS: 41556-26-7 EC: 255-437-1 Index: Non-applicable REACH: Non-applicable	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate <sup>[1]</sup>	Self-classified	0,1 - <1 %
Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning	 	

<sup>[1]</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -

**SECTION 4: FIRST AID MEASURES (continued)**

- 4.2 Most important symptoms and effects, both acute and delayed:**  
Acute and delayed effects are indicated in sections 2 and 11.
- 4.3 Indication of any immediate medical attention and special treatment needed:**  
Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

- 5.1 Extinguishing media:**  
**Suitable extinguishing media:**  
If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).  
**Unsuitable extinguishing media:**  
IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.
- 5.2 Special hazards arising from the substance or mixture:**  
As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.
- 5.3 Advice for firefighters:**  
Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.  
**Additional provisions:**  
Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions, protective equipment and emergency procedures:**  
**For non-emergency personnel:**  
Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.  
**For emergency responders:**  
See section 8.
- 6.2 Environmental precautions:**  
Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.
- 6.3 Methods and material for containment and cleaning up:**  
It is recommended:  
Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.
- 6.4 Reference to other sections:**  
See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

- 7.1 Precautions for safe handling:**  
A.- Precautions for safe manipulation  
Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.  
B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -



**SECTION 7: HANDLING AND STORAGE (continued)**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	1 mg/m³	Non-applicable	0,5 mg/m³
Hydrocarbons, C9, aromatics (Benzene < 1 % w/w) CAS: 128601-23-0 EC: Non-applicable	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m³	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C9, aromatics (Benzene < 1 % w/w) CAS: 128601-23-0 EC: Non-applicable	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m³	Non-applicable

**PNEC:**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	STP	88 mg/L	Fresh water	0,127 mg/L	
	Soil	53183 mg/kg	Marine water	0,013 mg/L	
	Intermittent	1,27 mg/L	Sediment (Fresh water)	266701 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg	

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

**GUARD PA PART B**  
**9115-0002B-2BA**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	 CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	29,2 % weight
V.O.C. density at 20 °C:	Non-applicable
Average carbon number:	9
Average molecular weight:	120 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**GUARD PA PART B**  
**9115-0002B-2BA**



**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Dense
Colour:	According to the markings on the package
Odour:	Characteristic
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	160 - 180 °C
Vapour pressure at 20 °C:	230 Pa
Vapour pressure at 50 °C:	1419,11 Pa (1,42 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1010 kg/m <sup>3</sup>
Relative density at 20 °C:	1,01
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	2500 mm <sup>2</sup> /s
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Insoluble
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	41 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	382 °C
Lower flammability limit:	0,7 % Volume
Upper flammability limit:	7,5 % Volume

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

**Other safety characteristics:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**A- Ingestion (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

**F- Specific target organ toxicity (STOT) - single exposure:**

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- CONTINUED ON NEXT PAGE -

**GUARD PA PART B**  
**9115-0002B-2BA****SECTION 11: TOXICOLOGICAL INFORMATION (continued)****G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Dose	
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate CAS: 41556-26-7 EC: 255-437-1	LD50 oral	2615 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	11,11 mg/L (4 h) (Calculation method)	39,6 %

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:****Acute toxicity:**

Identification	Concentration		Species	Genus
	Route	Dose		
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C9, aromatics (Benzene < 1 % w/w) CAS: 128601-23-0 EC: Non-applicable	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae

- CONTINUED ON NEXT PAGE -





## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Mixture of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylololol CAS: Non-applicable EC: 400-830-7	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate CAS: 41556-26-7 EC: 255-437-1	LC50	0.97 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	20 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

## 12.2 Persistence and degradability:

Not available

## 12.3 Bioaccumulative potential:

Not available

## 12.4 Mobility in soil:

Not available

## 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

## 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

## Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

## Regulations related to waste management:



In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

## Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

		14.1 UN number:	UN1263
		14.2 UN proper shipping name:	PAINT
		14.3 Transport hazard class(es):	3
		Labels:	3
		14.4 Packing group:	III
		14.5 Environmental hazards:	Yes
		14.6 Special precautions for user	
		Special regulations:	163, 367, 650
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

- CONTINUED ON NEXT PAGE -



**SECTION 14: TRANSPORT INFORMATION (continued)**

**Transport of dangerous goods by sea:**

With regard to IMDG 39-18:

	<b>14.1 UN number:</b>	UN1263
	<b>14.2 UN proper shipping name:</b>	PAINT
	<b>14.3 Transport hazard class(es):</b>	3
	<b>Labels:</b>	3
	<b>14.4 Packing group:</b>	III
	<b>14.5 Marine pollutant:</b>	Yes
	<b>14.6 Special precautions for user</b>	
	Special regulations:	223, 955, 163, 367
	EmS Codes:	F-E, S-E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
	Segregation group:	Non-applicable
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2021:

	<b>14.1 UN number:</b>	UN1263
	<b>14.2 UN proper shipping name:</b>	PAINT
	<b>14.3 Transport hazard class(es):</b>	3
	<b>Labels:</b>	3
	<b>14.4 Packing group:</b>	III
	<b>14.5 Environmental hazards:</b>	Yes
	<b>14.6 Special precautions for user</b>	
	Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable	

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

- CONTINUED ON NEXT PAGE -

**SECTION 15: REGULATORY INFORMATION (continued)**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed

(b) intermediate level training, including on-line training, on:

- additional behaviour-based aspects
- maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
- certification or documented proof that training has been successfully completed

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

### GUARD PA PART B 9115-0002B-2BA



#### SECTION 15: REGULATORY INFORMATION (continued)

(c) advanced training, including on-line training, on:

- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

#### SECTION 16: OTHER INFORMATION

##### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

##### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

##### Texts of the legislative phrases mentioned in section 2:

- H317: May cause an allergic skin reaction.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H411: Toxic to aquatic life with long lasting effects.
- H226: Flammable liquid and vapour.

##### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

##### CLP Regulation (EC) No 1272/2008:

- Acute Tox. 4: H332 - Harmful if inhaled.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- STOT SE 3: H335 - May cause respiratory irritation.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

##### Classification procedure:

- Skin Sens. 1: Calculation method
- STOT SE 3: Calculation method
- STOT SE 3: Calculation method
- Aquatic Chronic 2: Calculation method
- Flam. Liq. 3: Calculation method (2.6.4.3)

##### Advice related to training:

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

### GUARD PA PART B 9115-0002B-2BA



#### SECTION 16: OTHER INFORMATION (continued)

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -