



**Globally Proven  
Construction Solutions**

# STONETECH® ADVANCED GROUT SEALER

STONETECH® ADVANCED GROUT SEALER is a quick and easy to use grout sealer which helps keep cement based grout looking new.



## FEATURES/BENEFITS

- Maximum protection against most stains
- Apply as early as 2 hours after grouting
- Continuous flow spray allows for wall-to-floor application
- Interior and exterior use

## USES

- Countertops
- Backsplashes
- Floors
- Walls

## MANUFACTURER

LATICRETE EUROPE S.R.L .

Via Viazza 1° Tronco nr 19

41043 Formigine (MO) – Italy

Ph. +39 059557680

info@laticreteurope.com

## EXPECTED WEAR

- Up to 5 years on interior surfaces
  - Up to 3 years on exterior surfaces
- For best results, reapply annually.

### Recommended Surfaces

Cement-based grout for natural stone, ceramic and porcelain tile.

### Approximate Coverage

- Up to 152 linear m per 383 g Can

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

PWMIR <1.50 g O<sub>3</sub>/g product (Clear coatings)

### Cautions

Consult SDS for more safety information.

- Inhalation:** Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
- Skin contact:** Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists. **Frostbite:** Do not remove clothes, but flush with copious amounts of lukewarm water. Call an ambulance and continue to flush during transportation to hospital.
- Eye contact:** Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
- Ingestion:** Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.

### Storage and Handling Instructions

**DANGER! EXTREMELY FLAMMABLE.** Contains naphtha (petroleum), hydrotreated heavy (64742-48-9) and propane (74-98-6) and butane (106-97-8) as propellants. Do not use near sources of ignition, heat, flame, spark, or live electrical equipment, or while smoking. Vapors can travel to distant ignition sources. **VAPOR HARMFUL.** Do not breathe vapors or spray mist. **USE ONLY IN A WELL-VENTILATED AREA.** If unsure whether area is well-ventilated, use NIOSH approved respirator with a combination HEPA/organic vapor cartridge. Prevent build-up of vapors by opening windows and doors and by using exhaust

fans. Intentional misuse by deliberately inhaling contents of this container may be **HARMFUL OR FATAL. HARMFUL OR FATAL IF SWALLOWED.** Do not ingest. **MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.** Avoid eye and skin contact.

For safest application, wear protective eyewear, gloves, long sleeves, and long pants. **CONTENTS UNDER PRESSURE.** Do not puncture, incinerate, or store above 49 °C. Exposure to heat or prolonged exposure to sunlight may cause bursting. Do not discard can in trash compactor or burn. Do not mix product with other chemicals. Rags, clothing, and other equipment wet with product may be combustible. Clean up promptly after job is complete. Remove any clothing that comes in contact with product. Allow rags and clothing to dry in well ventilated area away from children and pets. When dry, dispose of rags. Wash affected clothing before re-wearing. **KEEP OUT OF THE REACH OF CHILDREN.** For professional or frequent use, a NIOSH-approved respirator with a HEPA/organic vapor cartridge is recommended. Consult product MSDS.

### TECHNICAL DATA

#### Physical Properties

|       |                |
|-------|----------------|
| Form  | Aerosol Liquid |
| Color | Clear          |
| Odor  | Solvent        |

#### Working Properties

|           |             |
|-----------|-------------|
| Full Cure | 24-48 hours |
|-----------|-------------|

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

### INSTALLATION

#### Surface Preparation

Read entire label before using. Use only as directed. Ensure area is well-ventilated during application and until surface is dry. Open windows and doors and use exhaust fans. Always test in a small inconspicuous area to determine appropriate application method and desired results. Avoid spraying surfaces not intended for treatment. For new installations, product can be applied as soon as 2 hours after grouting.

For best results, wait 4 hours or more. Grout should be firm to the touch before application. For cured

installations, grout must be clean, dry, and free of sealers and coatings. Keep children and pets out of the area until surface use resumes.

### Directions

1. Shake can well before using.
2. Hold can with extended arm 10 to 16 inches (254-406 mm) from the grout surface, aim nozzle, and spray STONETECH ADVANCED GROUT SEALER evenly along the grout line. Keep can tilted to assure even product distribution.
3. After 10 to 15 minutes, wipe entire surface with dry cloth to remove excess sealer. If using on newly applied grout, wipe lightly to avoid disturbing grout.
4. Dried residue from excess sealer can be removed from tile surfaces by wiping with a dry cloth.
5. A second coat is recommended and may be applied within one hour of initial application.
6. On cured grout, surface traffic may begin 2-6 hours after final application. For newly installed grout, follow grout manufacturer's guidance. It is required to keep the installation dry for a minimum of 12 hours.

## AVAILABILITY AND COST

### Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l. Telephone +39 059557680. For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu)

### Cost

Contact a LATICRETE® closer distributor to obtain complete information and cost.

## WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year.

Contact Technical Support for further information.

## MAINTENANCE

LATICRETE® products are of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

## TECHNICAL SERVICES

### Technical assistance

For information contact: +39 059557680

[info@laticreteurope.com](mailto:info@laticreteurope.com)

### Technical and safety literature

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu)

### Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® unable to directly control the installation conditions and modalities of application of products, do not assume any liability arising from their implementation. Those who want to use the LATICRETE® products must conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.