



# FLAKE

Blended Vinyl Fakes are especially designed blends to be used with GUARD PA PURE applications.

**Globally Proven  
Construction Solutions**



## FEATURES/BENEFITS

- Available in 3mm and 1mm sizes
- Highly Decorative Solutions
- Fire Resistant
- Lightweight.
- Interior Use
- Non-Toxic, very low VOC and no dust.
- Easy to Apply

## USES

- Interior and exterior
- Floors
- Increased traction

## MANUFACTURER

LATICRETE EUROPE S.R.L .

Via Viazza 1° Tronco nr 19

41043 Formigine (MO) – Italy

Ph. +39 059557680

info@laticreteeuropa.com

## STANDARDS/CERTIFICATIONS

Meets Émissions dans L'air Intérieur France



**Suitable Substrates**

As per Polyaspartic Coating

**Packaging**

- 20 Kg box

**Approximate Coverage**

Single Broadcast: 200 ft<sup>2</sup> (18.8 m<sup>2</sup>) / 50 lb bag

Double Broadcast: 100 ft<sup>2</sup> (9.4 m<sup>2</sup>) / 50 lb bag

**Shelf Life**

Unlimited, if stored in a dry place and in its original packaging +5°C - 20°C. Do Not Freeze.

**Color**

Six Blended Colours

**Limitations**

Refer to data sheet for applicable Polyaspartic Coatings

**Cautions**

- Refer to Safety Data Sheet (SDS)
- Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

**TECHNICAL DATA****Sieve Specification On Blended Colours**

Size 3mm

Fraction (Mm)	Weight-Percentage (%)
0.00 – 0.25	<2%
00.25 – 0.50	5 -15 %
0.50 – 1.00	55 -65 %
1.00 – 1.40	20 -30 %
> 1,40	< 1 %

**Properties**

Specific Weight : 2,0 – 2,5 G/Cm<sup>3</sup>

Binder : Pvc

Formaldehyde : < 10ppm

Voc : <1g/L

Flexibility : High

Light-Fastness : Low

**INSTALLATION**

FLAKE is to be broadcast by hand directly into consistently applied wet resin. Product should be left alone until underlying broadcast coat is completely dry.

**APPLICATION**

FLAKE can be applied by full broadcast and normal application methods. It is advisable to use a similar colour pigment primer to the blend required.

After use, brush off excess flakes and finish with transparent topcoat. Ensure that the surface is kept free of any contaminants (dirty footwear, tools etc.) until the resin has cured.

Can be used on both floor and wall applications.

**AVAILABILITY AND COST****Availability**

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l. Telephone +39 059557680. For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu)

**Cost**

Contact a LATICRETE® closer distributor to obtain complete information and cost.

**WARRANTY**

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year.

Contact Technical Support for further information

**MAINTENANCE**

LATICRETE® products are of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

**TECHNICAL SERVICES****Technical assistance**

For information contact: +39 059557680

[info@laticreteeuropa.com](mailto:info@laticreteeuropa.com)

**Technical and safety literature**

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu)

**Warning**

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® unable to directly control the installation conditions and modalities of application of products, do not assume any liability arising from their implementation. Those who want to use the LATICRETE® products must conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.