



SPARTACOTE™ Blended Chip

DS-086.3-0217

A product brand of LATICRETE International, Inc.



1. PRODUCT NAME

SPARTACOTE™ Blended Chip

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010
Toll Free: 1.866.966.1329
Toll Free Fax: 1.855.683.7257
Website: www.laticrete.com

3. PRODUCT DESCRIPTION

SPARTACOTE utilizes decorative vinyl color chips, are specially blended for SPARTACOTE Blended Chip and SPARTACOTE Blended Chip PURE seamless, resin-based chip flooring systems. This unique product is random in shape, sized within a standardized range and custom blended to match any décor.

Designed to increase durability and longevity while offering a high quality finish, our chips continue to gain popularity amongst architects, designers, contractors and consumers. They allow for customization to commercial, residential and industrial floors with an endless range color-styles, texture, size and blending options.

Advantages

- Available in standard vinyl as well as mica
- Good flexibility and strength
- Renewable and sanitary
- Easy to install
- Non-flammable
- Fully compatible with polyaspartic resins
- may be used to help hide small substrate imperfections

Suitable Substrates

- Refer to specific SPARTACOTE Coating Data Sheet

Packaging

Standard Chip: 55 lb (25 kg) box

Mica Chip: 25 lb (11.3 kg) box

Approximate Coverage

Standard Chip: 400 sq ft/55 lb (37.2 m²/25 kg) box

Mica Chip: 200 sq ft/55 lb (18.6 m²/25 kg) box

Shelf Life

Unlimited. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun). Take special care into ensuring that chip is not exposed to moisture.

Limitations

- Keep SPARTACOTE Blended Chip out of the sun and at ambient temperature during use. Follow temperature guidelines for specific SPARTACOTE Coating being used.
- SPARTACOTE Blended Chip may fade or shrink if exposed to excess sunlight or high temperatures.
- Please note that with all resinous coating systems, exterior full sun environments in warm climates may exhibit above average surface temperatures. This is especially true with darker finishes. As a result, resinous systems may not be ideally suited for exterior pool deck applications.

Cautions

- Refer to Safety Data Sheet (SDS)

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

4. TECHNICAL DATA

Applicable Standards and Test Methods

Working and Physical Properties

Size	1/8" - 1/4" (3.2 - 6.4 mm)
Thickness	5 mils DFT

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and

completeness of said tests are not guaranteed and are not be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE International, Inc. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

DS 230.13: LATICRETE Product Warranty
TDS 420: SPARTACOTE Floor Maintenance Guide

5. INSTALLATION

Please consult the SPARTACOTE™ system Application Guide for SPARTACOTE Chip and SPARTACOTE Chip PURE system prior to use.

Broadcast:

SPARTACOTE Blended Chip or SPARTACOTE Mica Chip is to be broadcast by hand directly into consistently applied wet resin. Product should be left alone until underlying broadcast coat is completely dry.

6. AVAILABILITY AND COST

Availability

SPARTACOTE and LATICRETE® materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.866.966.1329

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.laticrete.com.

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 420 “SPARTACOTE Floor Maintenance Guide” available at www.laticrete.com for more information.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.866.966.1329

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at www.laticrete.com. The following is a list of related documents:

SPARTACOTE
A product brand of LATICRETE International, Inc.
LATICRETE International, Inc. - One LATICRETE Park North, Bethany, CT 06524-3423 USA - 1.800.243.4788 - +1.203.393.0010 - www.laticrete.com
©2016 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.