

CLASSIFICATION: 09 67 00

PRODUCT DESCRIPTION: A high solids, low VOC and minimal odor resinous floor coating for both decorative and protective applications. SPARTACOTE FLEX XPL has been engineered to retain a low viscosity for longer periods of time, allowing for extended working times and better flow. It can be applied in single or multiple coats by brush roller or squeegee. SPARTACOTE FLEX XPL provides optimal impact, abrasion, and chemical resistance characteristics. Suitable for high traffic applications. The material is ideal for use as a primer, mid coat, or clear top coat sealer within resinous flooring applications requiring minimal installation odor.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold level

- 100 ppm
- 1,000 ppm
- Per GHS SDS
- Per OSHA MSDS
- Other

Residuals/Impurities

- Considered
- Partially Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities?
 Yes No

All Substances Above the Threshold Indicated Are:

Characterized Yes Ex/SC Yes No

% weight and role provided for all substances.

Screened Yes Ex/SC Yes No

One or more substances not screened using Priority Hazard Lists with results disclosed and/ or one or more Special Condition did not follow guidance.

Identified Yes Ex/SC Yes No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

SPARTACOTE® FLEX PURE™ XPL [SECONDARY DIAMINES Not Screened | SKI | HEXAMETHYLENE DIISOCYANATE HOMOPOLYMER (HDI HOMOPOLYMER) LT-P1 | DIPROPYLENE GLYCOL METHYL ETHER ACETATE (DPMA) LT-UNK | A MIXTURE OF: α-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-ω-HYDROXYPOLY(OXYETHYLENE); α-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-ω-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY NoGS OLY(OXY-1,2-ETHANEDIYL), ALPHA-(3-(3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXYPHENYL)-1-OXOPROPYL)-OMEGA-HYDROXY- NoGS DECANEDIOIC ACID, BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) ESTER; LT-P1 | PBT | MUL METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE LT-P1 | MUL 1,6-HEXAMETHYLENE DIISOCYANATE LT-UNK | RES | SKI | EYE | MAM]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This HPD was Created with Basic Inventory. Materials listed as Undisclosed in Section 2 is done to preserve integrity of formula and maintain competitive advantage. The component CAS# or SDS was used to identify and report associated hazards of these components.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 30.1 Regulatory (g/l): 30.1

Does the product contain exempt VOCs: No

Are ultra-low VOC tints available: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A

VOC content: TDS 251 "Low VOC LATICRETE Products"

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?

Yes

No

PREPARER: **Self-Prepared**

VERIFIER:

VERIFICATION #:

SCREENING DATE: **2018-08-13**

PUBLISHED DATE: **2018-12-19**

EXPIRY DATE: **2021-08-13**



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

SPARTACOTE® FLEX PURE™ XPL

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are measured by quantitative methods and are only displayed when they are potentially greater than 100 ppm.

OTHER PRODUCT NOTES: See SDS at <https://laticrete.com> for occupational exposure information. Materials listed as Undisclosed in Section 2 is done to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards of these components.

SECONDARY DIAMINES

ID: Not Registered

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-08-13

%: 65.0000 - 75.0000	GS: Not Screened	RC: None	NANO: No	ROLE: Curing Agent
----------------------	------------------	----------	----------	--------------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
Hazard Screening not performed		

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture. Component manufacturer does not provide CAS# which is stated as a Trade Secret. Hazards associated with this material were taken from component SDS.

HEXAMETHYLENE DIISOCYANATE HOMOPOLYMER (HDI HOMOPOLYMER)

ID: 28182-81-2

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-08-13

%: 20.0000 - 30.0000	GS: LT-P1	RC: None	NANO: No	ROLE: Curing Agent
----------------------	-----------	----------	----------	--------------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
No hazards found		

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture.

DIPROPYLENE GLYCOL METHYL ETHER ACETATE (DPMA)

ID: 88917-22-0

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2018-08-13

%: 4.0000 - 14.0000	GS: LT-UNK	RC: None	NANO: No	ROLE: Solvent
---------------------	------------	----------	----------	---------------

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
No hazards found		

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture.

A MIXTURE OF: α -3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL- ω -HYDROXPOLY(OXYETHYLENE); α -3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL- ω -3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY ID: **Not Registered**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2018-08-13**

%: **0.2000 - 0.3000** GS: **NoGS** RC: **None** NANO: **No** ROLE: **UV Stabilizer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
No hazards found		

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture.

OLY(OXY-1,2-ETHANEDIYL), ALPHA-(3-(3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXYPHENYL)-1-OXOPROPYL)-OMEGA-HYDROXY- ID: **Not Registered**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2018-08-13**

%: **0.2000 - 0.3000** GS: **NoGS** RC: **None** NANO: **No** ROLE: **UV Stabilizer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
No hazards found		

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture.

DECANEDIOIC ACID, BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) ESTER; ID: **41556-26-7**

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2018-08-13**

%: **0.1000 - 0.3000** GS: **LT-P1** RC: **None** NANO: **No** ROLE: **UV Stabilizer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
PBT	EC - CEPA DSL	Persistent, Bioaccumulative and inherently Toxic (PBiTE) to the Environment (based on aquatic organisms)
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters

SUBSTANCE NOTES: The amount of this component may vary based on the plant of manufacture.

METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE ID: **82919-37-7**

#: **0.0800 - 0.1500** GS: **LT-P1** RC: **None** NANO: **No** ROLE: **UV Stabilizer**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
MULTIPLE	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters

SUBSTANCE NOTES: **The amount of this component may vary based on the plant of manufacture.**

1,6-HEXAMETHYLENE DIISOCYANATE

ID: **822-06-0**

#: **0.0300 - 0.0800** GS: **LT-UNK** RC: **None** NANO: **No** ROLE: **Curing Agent**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagen (G) - generally accepted
SKIN IRRITATION	EU - GHS (H-Statements)	H315 - Causes skin irritation
SKIN SENSITIZE	EU - GHS (H-Statements)	H317 - May cause an allergic skin reaction
EYE IRRITATION	EU - GHS (H-Statements)	H319 - Causes serious eye irritation
MAMMALIAN	EU - GHS (H-Statements)	H331 - Toxic if inhaled
RESPIRATORY	EU - GHS (H-Statements)	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
RESPIRATORY	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization

SUBSTANCE NOTES: **The amount of this component may vary based on the plant of manufacture.**

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

N/A

CERTIFYING PARTY: **Self-declared**

ISSUE DATE: **2019-**

EXPIRY DATE:

CERTIFIER OR LAB: **LATICRETE**

APPLICABLE FACILITIES: **Applies to All Facilities.**

12-19

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: **SPARTACOTE™ FLEX XPL has not been tested for VOC emissions.**

VOC CONTENT

TDS 251 "Low VOC LATICRETE Products"

CERTIFYING PARTY: **Self-declared**

ISSUE DATE: **2018-**

EXPIRY DATE:

CERTIFIER OR LAB: **LATICRETE**

APPLICABLE FACILITIES: **Applies to All Facilities.**

06-13

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: **Meets LEED v4 "Low Emitting Materials" VOC content requirements.**

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

SPARTACOTE® FLEX PURE™ XPL meets the Living Building Challenge requirement that the product does not contain any of the Red Listed Materials or Chemicals. Specifically, SPARTACOTE FLEX PURE XPL does not contain the following: •Alkylphenols* •Asbestos •Bisphenol A (BPA)* •Cadmium •Chlorinated Polyethylene & Chlorosulfonated Polyethylene •Chlorobenzenes* •Chlorofluorocarbons (CFCs) & Hydrochlorofluorocarbons (HCFCs)* •Chloroprene (Neoprene) •Chromium VI* •Chlorinated Polyvinyl Chloride (CPVC)* •Formaldehyde (all types - added) •Halogenated Flame Retardants (HFRs) •Lead (added) •Mercury •Polychlorinated Biphenyls (PCBs)* •Perfluorinated Compounds (PFCs)* •Phthalates •Polyvinyl Chloride (PVC) •Polyvinylidene Chloride (PVDC)* •Short Chain Chlorinated Paraffins* •Wood treatments containing Creosote, Arsenic or Pentachlorophenol. SPARTACOTE FLEX PURE XPL also does not contain the following California-defined Group II toxic exempt solvents: •Methylene Chloride (Dichloromethane) •1,1,1-trichloroethane (methyl chloroform) •Trichlorofluoromethane (CFC-11) •Dichlorofluoromethane (CFC-12) •1,1,2-trichloro-1,2,2-trifluoroethane (CFC-113) •1,2-dichloro-1,1,2,2-tetrafluoroethane (CFC-114) •Chloropentafluoroethane (CFC-115) •Cyclic, Branched or Linear, Completely Methylated Siloxanes •(VMS) •Tetrachloroethylene (perchloroethylene) •Ethylfluoride (HFC-161) •1,1,1,3,3,3-hexafluoropropane (HFC-236fa) •1,1,2,3,3-pentafluoropropane (HFC-245ca) •1,1,2,3,3-pentafluoropropane (HFC-245ea) •1,1,1,2,3-pentafluoropropane (HFC-245eb) •1,1,1,3,3-pentafluoropropane (HFC-245fa) •1,1,1,2,3,3-hexafluoropropane (HFC-236ea) •1,1,1,3,3-pentafluorobutane (HFC-365mfc) •chlorofluoromethane (HCFC-31) •1,2-dichloro-1,1,2-trifluoroethane (HCFC-123a) •1 chloro-1-fluoroethane (HCFC-151a)



MANUFACTURER INFORMATION

MANUFACTURER: **LATICRETE International**
 ADDRESS: **1 Laticrete Park North**
Bethany CT 06524, US
 WEBSITE: **https://laticrete.com**

CONTACT NAME: **Mitch Hawkins**
 TITLE: **Senior Manager, Technical Service**
 PHONE: **2033934619**
 EMAIL: **wmhawkins@laticrete.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity	GLO Global warming	PHY Physical Hazard (reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive toxicity
DEV Developmental toxicity	MUL Multiple hazards	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	OZO Ozone depletion	LAN Land Toxicity
GEN Gene mutation	PBT Persistent Bioaccumulative Toxic	NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible Benchmark 1
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator Likely Benchmark 1
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS Unknown (no data on List Translator Lists)
BM-U Benchmark Unspecified (insufficient data to benchmark)	

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.