

CLASSIFICATION: 09 34 00

PRODUCT DESCRIPTION: A non-woven polyester fabric which is embedded into LATICRETE roller applied liquid rubber that together forms a waterproofing membrane/anti-fracture membrane for use under thin & thick bed installations of ceramic tile and stone, and other finishes.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
 Basic Method

Threshold Disclosed Per

- Material
 Product

Threshold level

- 100 ppm
 1,000 ppm
 Per GHS SDS
 Per OSHA MSDS
 Other

Residuals/Impurities

- Considered
 Partially Considered
 Not Considered

Explanation(s) provided
for Residuals/Impurities?

- Yes No

Are All Substances Above the Threshold Indicated:

Characterized Yes No
Percent Weight and Role Provided?

Screened Yes No
Using Priority Hazard Lists with Results Disclosed?

Identified Yes No
Name and Identifier Provided?

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

[MATERIAL](#) | [SUBSTANCE](#) | [RESIDUAL OR IMPURITY](#)
[GREENSCREEN SCORE](#) | HAZARD TYPE

[LATICRETE WATERPROOFING/ANTI-FRACTURE FABRIC \[POLYESTER](#)
[NoGS \]](#)

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen
Benchmark or List translator Score ... UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This HPD was Created with Basic Inventory. Materials listed as Undisclosed in Section 2 is done to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards of these components.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL GreenGuard (9235)

VOC content: TDS 251 "Low VOC LATICRETE® Products"

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1 and Option 2

Third Party Verified?

- Yes
 No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2018-07-27

PUBLISHED DATE: 2018-07-27

EXPIRY DATE: 2021-07-27



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

LATICRETE WATERPROOFING/ANTI-FRACTURE FABRIC

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are measured by quantitative methods and are only displayed when they are potentially greater than 100 ppm.

OTHER PRODUCT NOTES: See SDS for LATICRETE 9235 Waterproofing Membrane at www.laticrete.com for occupational exposure information.

POLYESTER

ID: 113669-95-7

#: 100.0000

GS: NoGS

RC: None

NANO: No

ROLE: Fabric

HAZARDS:

AGENCY(IES) WITH WARNINGS:

None Found

No warnings found on HPD Priority lists

SUBSTANCE NOTES: Required for installations of LATICRETE 9235 Waterproofing Membrane, LATICRETE Blue 92 Anti-Fracture Membrane and other LATICRETE membranes as specified.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

UL GreenGuard (9235)

CERTIFYING PARTY: **Third Party**

ISSUE DATE: **2009-**

EXPIRY DATE: **2017-**

CERTIFIER OR LAB: **UL**

APPLICABLE FACILITIES: **Applies to All Facilities.**

07-07

12-09

Environment

CERTIFICATE URL:

<http://certificates.ulenvironment.com/default.aspx?id=2538&t=cs>

CERTIFICATION AND COMPLIANCE NOTES: **Meets LEED v4 Credit "Low Emitting Materials" Emissions and Content Requirements**

VOC CONTENT

TDS 251 "Low VOC LATICRETE® Products"

CERTIFYING PARTY: **Self-declared**

ISSUE DATE: **2016-**

EXPIRY DATE:

CERTIFIER OR LAB: **LATICRETE**

APPLICABLE FACILITIES: **Applies to all facilities.**

07-07

CERTIFICATE URL:

<https://www.laticrete.com/~media/support-and-downloads/technical-datasheets/tds251.ashx?la=en>

CERTIFICATION AND COMPLIANCE NOTES: **Meets LEED v4 Credit "Low Emitting Materials" Emissions and Content Requirements.**

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

LATICRETE 9235 WATERPROOFING MEMBRANE

HPD URL: **No HPD link provided**

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

LATICRETE Waterproofing/Anti-Fracture Fabric must be used with LATICRETE 9235 Waterproofing Membrane, LATICRETE Blue 92 Anti-Fracture Membrane or other LATICRETE membranes following the directions as stated in the product data sheet.

Section 5: General Notes

LATICRETE® Waterproofing/Anti-Fracture Fabric meets the Living Building Challenge requirement that the product does not contain any of the Red Listed Materials or Chemicals. Specifically, LATICRETE Waterproofing/Anti-Fracture Fabric does not contain the following: •Alkylphenols* •Asbestos •Bisphenol A (BPA)* •Cadmium •Chlorinated Polyethylene & Chlorosulfonated Polyethylene •Chlorobenzenes* •Chlorofluorocarbons (CFCs) & Hydrochlorofluorocarbons (HCFCs)* •Chloroprene (Neoprene) •Chromium VI* •Chlorinated Polyvinyl Chloride

(CPVC)* •Formaldehyde (all types - added) •Halogenated Flame Retardants (HFRs) •Lead (added) •Mercury
•Polychlorinated Biphenyls (PCBs)* •Perfluorinated Compounds (PFCs)* •Phthalates •Polyvinyl Chloride (PVC)
•Polyvinylidene Chloride (PVDC)* •Short Chain Chlorinated Paraffins* •Wood treatments containing Creosote,
Arsenic or Pentachlorophenol. LATICRETE Waterproofing/Anti-Fracture Fabric also does not contain the following
California-defined Group II toxic exempt solvents: •Methylene Chloride (Dichloromethane) •1,1,1-trichloroethane
(methyl chloroform) •Trichlorofluoromethane (CFC-11) •Dichlorofluoromethane (CFC-12) •1,1,2-trichloro-1,2,2-
trifluoroethane (CFC-113) •1,2-dichloro-1,1,2,2-tetrafluoroethane (CFC-114) •Chloropentafluoroethane (CFC-115)
•Cyclic, Branched or Linear, Completely Methylated Siloxanes •(VMS) •Tetrachloroethylene (perchloroethylene)
•Ethylfluoride (HFC-161) •1,1,1,3,3,3-hexafluoropropane (HFC-236fa) •1,1,2,3,3-pentafluoropropane (HFC-245ca)
•1,1,2,3,3-pentafluoropropane (HFC-245ea) •1,1,1,2,3-pentafluoropropane (HFC-245eb) •1,1,1,3,3-
pentafluoropropane (HFC-245fa) •1,1,1,2,3,3-hexafluoropropane (HFC-236ea) •1,1,1,3,3-pentafluorobutane (HFC-
365mfc) •chlorofluoromethane (HCFC-31) •1,2-dichloro-1,1,2-trifluoroethane (HCFC-123a) •1 chloro-1-fluoroethane
)HCFC-151a)



MANUFACTURER INFORMATION

MANUFACTURER: **LATICRETE International**
ADDRESS: **1 Laticrete Park North**
Bethany CT 06524, USA
WEBSITE: **www.laticrete.com**

CONTACT NAME: **Mitch Hawkins**
TITLE: **Technical Services Manager**
PHONE: **203-393-4619**
EMAIL: **wmhawkins@laticrete.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet
GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity	GLO Global warming	PHY Physical Hazard (reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive toxicity
DEV Developmental toxicity	MUL Multiple hazards	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	OZO Ozone depletion	LAN Land Toxicity
GEN Gene mutation	PBT Persistent Bioaccumulative Toxic	NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible Benchmark 1
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator Likely Benchmark 1
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS Unknown (no data on List Translator Lists)
BM-U Benchmark Unspecified (insufficient data to benchmark)	

Recycled Types

PreC Preconsumer (Post-Industrial)
PostC Postconsumer
Both Both Preconsumer and Postconsumer
Unk Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.