



SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATICRETE@245 Concrete Patching Powder, 272, 290, Floor 'N Wall
Thinset Mortar (formerly under Dry Bond Trade Name)
CHEMICAL FAMILY:

Manufacturer/ Importer/ Supplier/ Distributor information Company

Name LATICRETE MIDDLE EAST LLC
Address P.O. Box. 86028, Ras Al Khaimah, United Arab Emirates
Telephone +971 7 244 6396
Contact person Mohmed Rafiq. M
Website www.laticrete.me/www.laticrete.com

II. HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Portland Cement	65997-15-1	50%	10 mg/m3	50 mppcf	N/A
Silica Sand*	14808-60-7	>1%	N/A	0.1 mg/m3	N/A
Dolomite+	16389-88-1	0-14%	10 mg/m3	50 mppcf	N/A

- IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans (volume 42, 1987) concludes that there is sufficient for the carcinogenicity of crystalline silica to experimental animals, and there is limited evidence of the carcinogenicity of crystalline silica to humans.

+ There are extremely small, but detectable amounts of substances regulated under California's Safe

Drinking water and Toxic Enforcement Act (Proposition 65)

- Arsenic – less than 2 ppm - Cadmium – less than 2 ppm
- Chromium (VI) – less than 0.1 ppm – Lead – less than 4 ppm

These levels are "typical" quantities and may change slightly with different lots. The term "less than"

Indicates that the Dolomite limestone contains crystalline silica at levels about 0.1% but less than 1%. These levels are "typical" and may change slightly with different lots.

N/A = Not applicable or available

III. PHYSICAL PROPERTIES

Vapour density (air =1): N/A

Melting point or range, F: N/A

Specific gravity: 1.40

Boiling point or range, F: N/A

Solubility in water: Insoluble

Evaporation rate (butyl acetate =1): N/A Vapour

pressure, mm Hg at 20 C: 0 mm

ph: N/A

Appearance and odor: Grey or white powder, odorless % Volatile by weight: N/A

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist):

This information is furnished without warranty, representation, inducement or license of any kind; Expect that it is accurate to the best of our knowledge, or obtained from sources believed by us to be Accurate.

LATICRETE@245 Concrete Patching Powder, 272, 290, Floor "N Wall Thinset Mortar

IV. FIRE AND EXPLOSION

Flash Point, F (give method): Not flammable or combustible

Auto ignition temperature: N/A

Flammable limits in air, volume %: N/A Lower (LEL) _____ Upper (UEL)

Fire extinguishing materials: N/A

_____ Water spray _____ carbon dioxide _____ other:

_____ foam _____ dry chemical

Special fire fighting procedures: N/A

Unusual fire and explosion hazards: None

V. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure. Inhaled:

Irritation of nose, cough, labored breathing, expectoration Contact with skin or eyes:

Irritation of eyes, skin sensitization Absorbed through skin: N/A

Swallowed : Expectoration

HEALTH EFFECTS OR RISKS FROM EXPOSURE. Ez plain in lay terms . Attach extra page if more space is needed:

Acute: Irritation of mucous membrane

Chronic: Chronic Bronchitis

FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately.

Skin Contact: Promptly wash contaminated skin with soap or mild detergent and water. Inhaled: Move the exposed person to fresh air at once.

Swallowed: If the person is conscious, give large quantities of water. After Swallowing water try to get person to vomit.
Get medical attention immediately.

SUSPECTED CANCER AGENT?

_____ NO: This product's ingredients are not found in the lists below. YES:

_____ Federal OSHA _____ NTP _____ X _____ IARC

LATICRETE@245 Concrete Patching Powder, 272,290, Floor "N Wall Thinset Mortar

VI. REACTIVITY DATA

Stability: _____ X _____ Stable _____ Unstable

Conditions to avoid: Keep dry until used Incompatibility (material to avoid): N/A

Hazardous decomposition products (including combustion products): None

Hazardous polymerization: _____ May occur _____ X _____ Will not occur

Conditions to avoid: n/a.

VII. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedure (include employee protection measures): Wear appropriate equipment to prevent skin and eyes contact; also a dust mask approved by NIOSH.

Preparing wastes for disposal (container types, neutralization, etc.): Sweep and / or shovel in to pails or drums with covers.

Note: Dispose of all wastes in accordance with federal, state and local regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: N/A

Respiratory protection (type): A NISOH approved dust mask Eye protection

(type): Chemical goggles or safely glasses Gloves(specify material): Use

impervious gloves, vinyl or rubber

Other clothing and equipment: Use appropriate clothing to prevent skin contact. Barries creams will assist in protecting the skin from contamination.

Work practices, hygienic practices: Familiarize the employees with the special handling procedures in this section; also encourage prompt removal of contaminated clothing or washing of contaminated areas.

Other handling and storage requirements: Store in a dry area

Protective measures during maintenance of contaminated equipment: Water gloves to prevent skin contamination.