

## **LATAPOXY®** 300



A high-strength, three-part, 100% solids epoxy adhesive formulated for chemical-resistant installations of quarry tile, brick, and packing house tile.

## **FEATURES/BENEFITS:**

- Prevents curling of moisture-sensitive marbles and agglomerates
- For mesh mount glass mosaics and resin-backed tile and stone
- Will not stain white or light colored marble
- Meets ANSI A118.3, EN 12004 and ISO 13007-1 R2 classification





Approximate Coverage Per#2 unit	
NOTCH TROWEL	COVERAGE
3 mm x 3 mm Square	5.6 - 6.5 m <sup>2</sup>
4mm - V Notch Trowel	3.7 - 4.6 m2
6 mm x 6 mm Square	2.8 - 3.3 m <sup>2</sup>

## PACKAGING:

All components packed in one pail;

Net weight - 11.1 Kg, Gross weight - 12.1 Kg; Makes 6.8 L of mortar.

48 pails per pallet.

† See Data Sheet for complete warranty information.



LATICRETE MIDDLE EAST LLC.| P.O Box: 86028 | Ras Al Khaimah | United Arab Emirates
Phone: + 971 7 244 6396 | + 971 4 331 99 72 | Fax: + 971 7 244 5915 | enquiry@laticrete.me

© 2019 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.

Latapoxy 300.indd 1 2/27/19 4:17 PM