



Globally Proven  
Construction Solutions

## LATAFINISH Wall Putty – Fine Finish

LATAFINISH Wall Putty is water resistant white cement based fine powder. After mixing with recommended quantity of water it forms a fine paste, which provides a very fine finish to walls and ceiling, ideal for use on Plastered / concrete walls and ceilings. It covers unevenness & pinholes of walls and provides smooth finish dry surfaces for painting.



### ADVANTAGES

- White smooth and glossy finish
- Highly durable & damp resistant
- Anti fungal.
- No needs of primer before applying paint.
- Strong adhesion strength.
- No curing required.
- Increases Paint Coverage

### MANUFACTURER

**LATICRETE Middle East LLC.**  
P.O. Box. 86028, Ras Al Khaimah  
United Arab Emirates  
Telephone: + 971 7 244 6396  
Fax: + 971 7 244 5915  
Internet: [www.laticrete.me](http://www.laticrete.me)

### USES

Designed for interior and exterior surfaces.  
To make uneven surfaces even and smooth  
Can be used on concrete, rendered wall, hollow block, precast walls, concrete ceilings, aerated light weight blocks.

### PACKAGING / COLOR

**Packaging,**  
20 kg bags, 72 bags per pallet  
**Color:** white

**Approximate Coverage**

12 to 15 Sq. ft (i.e. 1.1 to 1.4 Sq. M) per Kg of Powder when mixed with water, for total approximate thickness of 1.5 mm in two coats.

20Kg bag of Powder will cover 22 to 28 Sq. M.

**Shelf Life**

Factory sealed bags of this product are guaranteed to be of first quality for 12 (twelve) months\* if stored off the ground in a dry area.

\* High humidity will reduce the shelf life of bagged product.

**Limitations**

- Do not directly apply on the fungus and moss affected areas.
- Do not apply directly on the dust, loosely bonded particles, oil, Grease etc affected surfaces.

Note: Surfaces must be two coated cement and smooth plaster, structurally sound and stable.

**Cautions**

- Though it contains non toxic material but still care should be taken to avoid dust inhalation while mixing and handling. In case of contact with eyes or mouth, flush thoroughly with plenty of water.
- Do not take internally. Avoid breathing dust.
- Keep out of reach of children

**TECHNICAL DATA****Applicable Standard**

HDB Singapore.

Test	Specification of HDB standard	Result	Standard method
Tensile adhesion strength @ 14 day	≥ 0.8 MPa	0.90 MPa	EN 1015:12
Setting time IST	240-360 mints	300 mints	EN 196
FST	≤ 500 mints	420 mints	
Water Absorption Kg/m <sup>2</sup> /√h	---	1	DIN 52617
Water retentivity	>95%	99.5%	BS 4551:1
Pot life	---	3-4hrs	---

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

**INSTALLATION****Preparation**

All Surfaces should be between 40°F (4°C) and 90°F (32°C) temp. It should be free from all dirt, oil, grease, loose sand particles. If it is old painted wall/lime washed wall then first scratch old surface. Dry and absorbent surfaces should be moistened/pre wet with clean water.

**Mixing**

Use approximately 8 to 10 L of fresh water for 20 kg Latafinish® Wall Putty i.e. Water to Powder ratio is approx. 40:100. Mix thoroughly till uniform (free from bubbles and lumps) paste occurs. Allow paste to slake for 5-10 minutes. Adjust consistency if necessary. Remix and apply with putty blades.

**Application**

Apply two coats of Latafinish Wall Putty on the substrate with maximum total thickness 1.5mm with the putty blades. Ensure that the second coat application should be done when the first coat is totally dried after min. 3hrs. Always prepare a required quantity of putty paste and use it within 2-3 hrs. To remove unevenness/ application mark and to make glossy surfaces before applying paint use water proof emery paper more than 500 number

**AVAILABILITY AND COST****Availability**

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE Telephone: For on-line distributor information, visit [www.laticrete.com](http://www.laticrete.com)

**Cost**

Contact a LATICRETE® closer distributor to obtain complete information and cost.

**WARRANTY**

LATICRETE Middle East LLC warrants that Latafinish Wall Putty is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of twelve (12) months from manufacturing of the product subject to the terms and conditions stated in LATICRETE Product Warranty.

**TECHNICAL SERVICES****Technical assistance**

For information contact:

[enquiry@laticrete.me](mailto:enquiry@laticrete.me)

**Technical and safety literature**

To obtain technical and safety literature, please visit our website at [www.me.laticrete.com](http://www.me.laticrete.com)