



SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE LATASIL 9118 Primer

Other means of identification None.

Recommended use of the chemical and restrictions on use

Recommended use Primer.

Restrictions on use Not available.

Details of manufacturer or importer

Manufacturer

Company name LATICRETE International
Address 1 Laticrete Park, N
 Bethany, CT 06524
Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com
Emergency phone number Call CHEMTREC day or night
 USA/Canada - 1.800.424.9300
 Mexico - 1.800.681.9531
 Outside USA/Canada
 1.703.527.3887

Supplier

Company name LATICRETE Middle East LLC
Address P.O. Box. 86028
 Ras Al Khaimah, United Arab Emirates
Telephone +971 7 244 6396
Website www.laticrete.me
Contact Person Mohmed Rafiq. M

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity following single exposure	Category 3 narcotic effects
	Specific target organ toxicity following repeated exposure	Category 2 (Central nervous system, Hearing organs)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3

Label elements, including precautionary statements

Hazard symbol(s)

Flame

Health hazard

Exclamation mark

Signal word

Danger

Hazard Statement(s)

Highly flammable liquid and vapour. Causes skin irritation. Suspected of causing cancer. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs (Central nervous system, Hearing organs) through prolonged or repeated exposure. Harmful to aquatic life.

Precautionary Statement(s)**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapour. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention. In case of fire: Use carbon dioxide for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information

None.

3. Composition/information on ingredients**Mixture**

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Propan-2-ol	67-63-0	10 - < 20
Toluene	108-88-3	10 - < 20
Alkoxysilane	Trade secret	5 - < 10
Ethylbenzene	100-41-4	3 - < 5
Xylene	1330-20-7	3 - < 5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures**Description of necessary first aid measures****Inhalation**

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

Skin contact

Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

Ingestion

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.

Personal protection for first-aid responders

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention.

Symptoms caused by exposure Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritant effects. May cause temporary blindness and severe eye damage.

Medical attention and special treatment Treat symptomatically. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical By heating and fire, harmful vapours/gases may be formed.

Special protective equipment and precautions for fire fighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

Hazchem Code 3 Y E

General fire hazards Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapour. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods and materials for containment and cleaning up ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Following product recovery, flush area with water. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Other issues relating to spills and releases Clean up in accordance with all applicable regulations.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. The product is highly flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapour. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Use Personal Protective Equipment recommended in section 8 of the SDS. Wash thoroughly after handling. Handle and open container with care.

Conditions for safe storage, including any incompatibilities Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m ³
		125 ppm
	TWA	434 mg/m ³
		100 ppm
Propan-2-ol (CAS 67-63-0)	STEL	1230 mg/m ³
		500 ppm
	TWA	983 mg/m ³
		400 ppm
Toluene (CAS 108-88-3)	STEL	574 mg/m ³
		150 ppm
	TWA	191 mg/m ³
		50 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m ³
		150 ppm
	TWA	350 mg/m ³
		80 ppm

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m ³
		125 ppm
	TWA	434 mg/m ³
		100 ppm
Propan-2-ol (CAS 67-63-0)	STEL	1230 mg/m ³
		500 ppm
	TWA	983 mg/m ³
		400 ppm
Toluene (CAS 108-88-3)	STEL	574 mg/m ³
		150 ppm
	TWA	191 mg/m ³
		50 ppm
Xylene (CAS 1330-20-7)	STEL	655 mg/m ³
		150 ppm
	TWA	350 mg/m ³
		80 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m ³

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)		125 ppm
	TWA	441 mg/m ³
		100 ppm
	STEL	1250 mg/m ³
Toluene (CAS 108-88-3)		500 ppm
	TWA	999 mg/m ³
		400 ppm
	STEL	384 mg/m ³
Xylene (CAS 1330-20-7)		100 ppm
	TWA	191 mg/m ³
		50 ppm
	STEL	441 mg/m ³
		100 ppm
	TWA	220 mg/m ³
		50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	88 mg/m ³
Propan-2-ol (CAS 67-63-0)		20 ppm
	TWA	500 mg/m ³
		200 ppm
Toluene (CAS 108-88-3)		190 mg/m ³
	TWA	50 ppm
		440 mg/m ³
Xylene (CAS 1330-20-7)		440 mg/m ³
	TWA	100 ppm

Biological limit values**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling time
Ethylbenzene (CAS 100-41-4)	300 mg/l	Mandelsäure plus Phenylglyoxylsäure	Urine	*
Propan-2-ol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*
Toluene (CAS 108-88-3)	600 µg/l	Toluol	Blood	*
	1.5 mg/l	o-Kresol (nach Hydrolyse)	Urine	*
Xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-)säure (alle Isomere)	Urine	*
	1.5 mg/l	Xylol	Blood	*

* - For sampling details, please see the source document.

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling time
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines Follow standard monitoring procedures.

Australia OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Appropriate engineering controls Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency shower.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear goggles/face shield.

Skin protection

Hand protection

Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance	Clear liquid.
Physical state	Liquid.
Form	Liquid.
Colour	Clear. Colourless.
Odour	Solvent odor.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	82.4 °C (180.32 °F) (Propan-2-ol)
Flash point	9.0 °C (48.2 °F) Tag closed cup
Evaporation rate	> 1 (Butyl acetate = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1 % (Xylene)
Flammability limit - upper (%)	7 % (Xylene)
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapour pressure	4.2 kPa (20 °C) (Propan-2-ol)

Vapour density	2.1 (air=1.0) (Propan-2-ol)
Relative density	0.98 (25 °C)
Solubility(ies)	
Solubility (water)	Insoluble in water. (Hydrolyzed with water)
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	200 mPa·s (25 °C)
Other physical and chemical parameters	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Reacts with water and moisture in air liberating methanol.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidising agents. Water. Acids. Alkalies.
Hazardous decomposition products	Methanol. Carbon monoxide. Carbon dioxide. Silicon dioxide. Formaldehyde.

11. Toxicological information

Information on possible routes of exposure

Inhalation	May cause drowsiness and dizziness. Headaches, nausea and vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Ingestion may cause irritation and malaise.

Symptoms related to exposure Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritant effects. May cause temporary blindness and severe eye damage.

Acute toxicity May cause discomfort if swallowed.

Components	Species	Test results
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15400 mg/kg
<i>Inhalation</i>		
LC50	Rat	17.4 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	3500 - 4700 mg/kg
Propan-2-ol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12870 mg/kg
<i>Inhalation</i>		
LC50	Rat	72.6 mg/l, 4 hours
<i>Oral</i>		
LD50	Rat	4710 mg/kg

Components	Species	Test results
Toluene (CAS 108-88-3)		
Acute		
<i>Inhalation</i>		
LC50	Rat	8000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
Acute		
<i>Oral</i>		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/irritation	Causes serious eye irritation.	
Respiratory or skin sensitisation		
Respiratory sensitisation	Not classified.	
Skin sensitisation	Not a skin sensitiser.	
Germ cell mutagenicity	Not classified.	
Carcinogenicity	Suspected of causing cancer.	
ACGIH Carcinogens		
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Propan-2-ol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.	
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Propan-2-ol (CAS 67-63-0)	3 Not classifiable as to its carcinogenicity to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to its carcinogenicity to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to its carcinogenicity to humans.	
Reproductive toxicity	Suspected of damaging the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (Central nervous system, Hearing organs) through prolonged or repeated exposure.	
Aspiration hazard	Not classified.	
Chronic effects	Xylene: May cause damage to the liver and kidneys.	
Other information	No other specific acute or chronic health impact noted.	

12. Ecological information

Ecotoxicity	Harmful to aquatic life.		
Components	Species	Test results	
Ethylbenzene (CAS 100-41-4)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4.2 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	EC50	Ceriodaphnia dubia	3.6 mg/l, 7 days
Propan-2-ol (CAS 67-63-0)			
Aquatic			
<i>Acute</i>			
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours

Components	Species	Test results
<i>Chronic</i> Crustacea	EC50 Daphnia magna	> 100 mg/l, 21 days
Xylene (CAS 1330-20-7)		
Aquatic Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours
Persistence and degradability	Expected to degrade rapidly in water due to hydrolysis. [Alkoxysilane].	
Bioaccumulative potential	No data available for this product.	
Partition coefficient n-octanol / water (log Kow)		
Ethylbenzene (CAS 100-41-4)	3.15	
Propan-2-ol (CAS 67-63-0)	0.05	
Toluene (CAS 108-88-3)	2.73	
Xylene (CAS 1330-20-7)	3.2	
Mobility in soil	Not available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

13. Disposal considerations

Disposal methods	Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.
Residual waste	Dispose in accordance with applicable federal, state, and local regulations.
Contaminated packaging	Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

ADG

UN number	1866
UN proper shipping name	Resin solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Not available.
Hazchem Code	•3YE
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

UN number	1866
UN proper shipping name	Resin solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	1866
UN proper shipping name	Resin solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	1866
UN proper shipping name	RESIN SOLUTION
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S</u> -E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	This product is not intended to be transported in bulk.
General information	IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

Safety, health and environmental regulations

National regulations This Material Safety Data Sheet was prepared in accordance with the Australia National Code of Practice for the Preparation of Material Safety Data Sheets (NOHSC: 2011.)

Australia Medicines & Poisons Appendix A

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix B

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix C

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix D

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix E

Toluene (CAS 108-88-3)

For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at once)., If swallowed, do NOT induce vomiting.

For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at once)., If swallowed, do NOT induce vomiting., If in eyes wash out immediately with water., If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water., If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

in pressurised spray packs For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at once).

For advice, contact a Poisons information Centre (Phone eg Australia 131 - 126; New Zealand 03 - 4747 - 000) or a doctor (at once)., If swallowed, do NOT induce vomiting.

Xylene (CAS 1330-20-7)

Australia Medicines & Poisons Appendix F

Toluene (CAS 108-88-3)

applies to all preparations in any concentration Avoid contact with eyes., Avoid contact with skin., Avoid breathing dust (or) vapour (or) spray mist.

Xylene (CAS 1330-20-7)

applies to all preparations in any concentration Avoid contact with eyes., Avoid contact with skin., Avoid breathing dust (or) vapour (or) spray mist.

Australia Medicines & Poisons Appendix G

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix H

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix I

Toluene (CAS 108-88-3)

Second Schedule.

Xylene (CAS 1330-20-7)

Second Schedule.

Australia Medicines & Poisons Appendix J

Poisons schedule number not allocated.

Australia Medicines & Poisons Appendix K

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 2

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 3

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 4

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 5

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

applies to all preparations in any concentration Exception may apply, see the regulation for relevance.

applies to all preparations in any concentration Exception may apply, see the regulation for relevance.

Australia Medicines & Poisons Schedule 6

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Exception may apply, see the regulation for relevance.

Exception may apply, see the regulation for relevance.

Australia Medicines & Poisons Schedule 7

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 8

Poisons schedule number not allocated.

Australia Medicines & Poisons Schedule 9

Poisons schedule number not allocated.

Australia National Pollutant Inventory (NPI): Threshold quantity

Ethylbenzene (CAS 100-41-4)

10 TONNES/YR Threshold Category: 1

Toluene (CAS 108-88-3)

10 TONNES/YR Threshold Category: 1

Xylene (CAS 1330-20-7)

10 TONNES/YR Threshold Category: 1

High Volume Industrial Chemicals (HVIC)

Propan-2-ol (CAS 67-63-0)

1000 - 9999 TONNES See the regulation for additional information.

Toluene (CAS 108-88-3)

10000 - 99999 TONNES See the regulation for additional information.

Xylene (CAS 1330-20-7)

10000 - 99999 TONNES See the regulation for additional information.

Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

Not listed.

National Pollutant Inventory (NPI) substance reporting list

Not listed.

Prohibited Carcinogenic Substances

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

Restricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

Restricted Carcinogenic Substances

Not regulated.

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 17-February-2016

Revision date -

References HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.