

ICC-ES PMG Listing**PMG-1005**

Effective Date: March 1, 2013

This listing is subject to re-examination in one year.

www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00 — PLUMBING
Section: 22 40 00 — Plumbing Fixtures

DIVISION: 09 00 00—FINISHES
Section: 09 30 00—Tiling

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system

Product: LATICRETE 9235 Waterproofing Membrane

Listee: LATICRETE International, Inc.
1 Laticrete Park North
Bethany, Connecticut 06524-3423
www.laticrete.com

Compliance with the following codes:

2012, 2009 and 2006 *International Residential Code*® (IRC)
2012, 2009 and 2006 *International Plumbing Code*® (IPC)
2012, 2009 and 2006 *Uniform Plumbing Code*® (UPC)*
1997 *Standard Plumbing Code*® (SPC)

Uniform Plumbing Code is a copyrighted publication of the International Association of the Plumbing and Mechanical Officials

Compliance with the following standard:

ANSI A118.10-2011, Standard Specification for Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension

ICC-ES AC115 Acceptance Criteria for Waterproof Membranes for Flooring and Shower Sub-Pan Lining (Editorially revised September 2011)

Identification:

Each packaging box of LATICRETE 9235 liquid membrane, reinforcement fabric, sealant and reinforcement tape described in this listing must be identified by a stamp bearing the manufacturer's name (LATICRETE International, Inc.), the product type, and either the ICC-ES evaluation report number (ESR-1058) or the ICC-ES PMG listing mark.

Installation:

LATICRETE 9235 Waterproofing Membrane must be installed in accordance with the manufacturer's published instructions and the applicable code(s).

Ceramic tile must comply with ANSI A137.1

Drains must have a clamping ring with open weep holes in accordance with ASME A112.6.3.

Models: LATICRETE 9235 liquid

A ready-to-use, 54-percent-solids, formulated, styrene butadiene, rubber-based latex, packaged in 6-gallon (22.7 L) pails.

LATICRETE 9235 reinforcing fabric

A 2.4-ounce-per-square-yard (75.7 g/m²) fabric for use as reinforcement in the LATICRETE 9235 Waterproofing Membrane. The fabric is provided in 300-square-foot (27.9 m²) rolls.

LATICRETE 9235 reinforcing tape

A 2.4-ounce-per-square-yard (75.7 g/m²) fabric for use in preparing joints and cracks of the substrate before application of the LATICRETE 9235 Waterproofing Membrane. The tape is provided in 6-inch-wide-by-75-foot-long (152 mm by 22 860 mm) rolls.

LATICRETE Latasil Tile and Stone Sealant

A silicone sealant for use with penetrations that come in contact with the LATICRETE 9235 Waterproofing Membrane. The sealant is provided in 10.3-ounce (305 mL) cartridges.

Conditions of Listing:

1. Application is limited to ceramic tile and dimension stone installations on floors, and to use as shower sub-pans or lining.
2. Control joints greater than 1/8 inch (3 mm), structural cracks and expansion joints with vertical differential movement used with the LATICRETE 9235 Waterproofing Membrane are outside the scope of this report.
3. LATICRETE 9235 Waterproofing Membrane is manufactured in Bethany, Connecticut, under a quality control program with annual surveillance inspections by ICC-ES.