



Blue 92 Anti-Fracture Membrane

www.laticrete.com

DS-711.0-0107



Private Residence, Woodbridge, CT
Architect: Inter-design Ltd., Old Lyme, CT
Contractor: Sasso Tile, West Haven, CT



- Prevent cracks in tile, marble and stone floors
- Isolates cracks up to 1/8" thick from transferring through substrate to floor finish
- Thin; adds no appreciable thickness to floor
- Inhibits the growth of stain-causing mold and mildew in the membrane with Microban® antimicrobial protection
- Easy to install; dries in 2 hours

LATICRETE® Blue 92 Anti-Fracture Membrane provides protection and peace of mind for contractors and builders. Too often tile or stone installations crack due to failure in the concrete substrate below. LATICRETE Blue 92 Anti-Fracture Membrane eliminates cracking

and delamination of tile or stone due to cracked and contaminated concrete. In addition, LATICRETE Blue 92 Anti-Fracture Membrane inhibits the growth of stain-causing mold and mildew in the membrane with Microban® antimicrobial protection.

| FEATURES | BENEFITS |
|--|--|
| TCA "Extra Heavy" Service Rating per ASTM C627 | Allows for successful application in heavy traffic areas such as malls, food plants and dairies without deterioration |
| Easy to Install, Applies Like Paint | Roller applied liquid is quick and easy to install over concrete; allows for fast job turnaround, saving time and labor |
| Safe, No Solvents | Non-flammable and easy to clean off surfaces while fresh with water; requires no special storage or handling procedures and contains no harsh fumes |
| Meets New ANSI 118.12 Specifications for Crack Isolation | Industry accepted performance for commercial and residential installations; isolates cracks up to 1/8" thick from transferring through substrate to the floor finish |
| Fast Drying | Ready for tiling in just 2 hours |
| A Component of the LATICRETE® Lifetime Residential Warranty and LATICRETE 10 Year System Warranty† | Performance backed by LATICRETE means peace of mind for trouble-free installations in both interior and exterior applications |
| Contains Microban® | Inhibits the growth of stain-causing mold and mildew in the membrane with Microban® antimicrobial protection |

Uses

- For interior or exterior use, floors and walls, whenever hairline cracking or "spiderwebbing" occurs in the substrate
- For use over shrinkage and other non-structural cracks up to 1/8" (3 mm)
- Typical applications are over concrete slabs (suspended or on grade) in malls, lobbies and residential applications under ceramic tile, marble and stone
- Use to cover joints in plywood underlayments, cement backer boards, and concrete masonry on floors and walls
- Also use over concrete floors and underlayments with radiant heating systems

Suitable Substrates

- Concrete
- Cement Terrazzo
- Mortar Beds, Renders
- Concrete Masonry
- Cement Backer Board**
- Exterior Glue Plywood*

* Interior applications only

** Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use

Packaging

Full Unit:

1 x 5 US gallon (19 ℓ) pail liquid

1 x 300 ft² (28 m²) roll fabric: 38" (965 mm) wide

1 x 75 ft (23 Lm) roll fabric: 6" (150 mm) wide

Mini Unit:

Crack Suppression Kit

1 x 2 US gallon (7.66 ℓ) jug liquid

1 x 75 ft (23 Lm) roll fabric: 15" (37.5 cm) wide

Approximate Coverage

Full Unit:

300 ft² (23 m²)

75 lft (23 lm) per crack suppression kit

LATICRETE INTERNATIONAL, INC.

One LATICRETE Park North

Bethany, CT 06524-3423 USA

800.243.4788

203.393.0010

www.laticrete.com

† See Data Sheets 700.12 and 230.12 for complete warranty information