



SPECTRALOCK® 1

Pre-Mixed Grout with Epoxy Performance

NEW



Data Sheet 36589.0



FEATURES	BENEFITS
Stainproof [^]	Locks in color, blocks out stains
10X stronger than other pre-mixed grouts	More durability, minimizing application failures
No mixing required, resealable packaging	Reduces waste and material costs
Meets ANSI A118.3 [‡]	As strong as epoxy; excellent stain and chemical resistance
Light foot traffic within 6 hours	Complete projects in less time
Submerged and intermittent wet applications	Ready to submerge in 14 days; Showers ready for use next day [*]
No efflorescence	Uniform color consistency; eliminating discoloring, blotches, and shading
Low VOC and low odor	Easy and safe to use with no epoxy resins
Optional SPECTRALOCK® DAZZLE™ component	Compliments tile and stone design

Uses


- Ceramic tile, glass tile and stone
- Residential and commercial
- Interior and exterior floors and walls^{^^}
- Ideal for re-grouting applications
- Submerged and intermittent wet areas

Available Colors

- All 40 LATICRETE colors[†]
- 12 SPECTRALOCK® DAZZLE™ options

Packaging

- 1 (3.8L) gallon^{*}



Snap for more information and the SPECTRALOCK 1 story.



[^]Stainproof (residential installation only) to common household cleaners, liquids and other goods. Clean all spills immediately.
[‡]Meets or exceeds ANSI A118.3 specific test designation 5.6
^{*}Refer to Data Sheet 36589.0 for limitations and complete packaging information.
[†]Not for exterior facades
^{**}Refer to LATICRETE® Grout Color Chart, Data Sheet 254.3 for complete color selection information.
^{^^}See Data Sheet 230.99 for complete warranty information.

