



STONETECH® DeepKlenz™ Cleaner

DS-111.2-0220

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® DeepKlenz™ Cleaner

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

STONETECH® DeepKlenz™ Cleaner is a maximum strength cleaner, formulated to easily remove deep and stubborn dirt, grease, grime, oil and food stains from natural stone, tile and grout. This ready-to-use, low VOC cleaner cleans, degreases and prepares the surface for resealing. It powers out dirty grout lines and is great for use in heavy traffic areas.

Uses

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Maximum strength cleaner
- Easily removes deep & stubborn grease, oils and food stains
- Cleans, degreases and prepares surface for resealing

- Water-based, alkaline formula
- Safe on stone
- Low VOC - Better indoor air quality

Suitable Substrates

- Marble
- Granite
- Quartzite
- Limestone
- Travertine
- Slate
- Sandstone
- Concrete
- Ceramic Tile
- Porcelain tile
- Stainless Steel
- Quartz
- Grout

Packaging

US

READY-TO-USE

ST439-0624-10: 24 fl oz (709ML) Spray Bottle - 6 units / case

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures <50°F (10°C) and >90°F (32°C).

Limitations

- May affect soundness of some paints, aluminum and glass.

Cautions

- Consult SDS for more safety information.
- STORAGE AND HANDLING INSTRUCTIONS:
- No special handling is required under normal use. Appropriate protective clothing necessary to prevent repeated or prolonged skin contact should be worn. Skin contact should be minimized by wearing

impermeable gloves. Resistant boots should be worn where spills or splashing can occur. Wash hands and other contaminated areas thoroughly with soap and water after handling this product and before eating or smoking. Wash contaminated clothing thoroughly before reuse. Safety showers and eye stations should be available to employees. Normal warehouse storage in a closed container is adequate. Storage temperature should be above freezing and below 120°F. Drain equipment and flush with water to clean.

- CORROSION: Avoid prolonged contact with aluminum. Avoid contact with magnesium.

4. TECHNICAL DATA



VOC/LEED Product Information

3.3% (Consumer Product)

Physical Properties

Form	Liquid
Color	Slightly amber, clear liquid
Odor	Organic ether odor
pH	10.5

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Directions

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of use and desired results. Make sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Keep children and pets out of the area during application and drying.

1. Thoroughly wet surface by directly spraying onto soiled area.
2. Allow STONETECH® DeepKlenz™ Cleaner to work on the surface for 5-10 minutes. Do NOT allow product to dry on the surface.
3. Lightly scrub with a stiff bristle brush to remove the surface contaminants.
4. Rinse and wipe surface with clean cloth and warm water. Repeat as needed for heavily soiled areas.
5. Reseal cleaned area with a STONETECH Sealer.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- DS.230.13: 1 Year Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For deep and stubborn dirt, grease and grime use STONETECH DeepKlenz™ Cleaner. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.