



# L&M™ CITREX™

DS-176.6-0622

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

L&M™ CITREX™

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235  
Toll Free: 1.800.243.4788, ext. 1235  
Fax: +1.203.393.1684  
Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

CITREX is a heavy duty, citrus based degreaser and cleaner for both specialized cleaning and every day maintenance. This pleasantly fragrant cleaner is formulated to include low foaming emulsifiers and degreasing agents in high concentrations. CITREX is concentrated to maintain high activity at various dilutions with water to effectively remove accumulations of built-up grease, grime, oil and rubber burns.

### Uses

Use CITREX to deeply penetrate surfaces to dissolve dirt and emulsify fats and greases quickly and easily in food processing plants, meat packing plants, canneries, restaurants, kitchens, bakeries, dairy, cheese and fish processors where thorough cleanliness is critical. CITREX is also effective in removing grime, oil and contaminants from concrete, masonry or other surfaces in parking garages, truck and automotive plants, warehouses, industrial plants, steel mills, sewage plants, or oil burning power plants. It is also recommended for

use in warehouses to remove rubber tire marks and other contaminants.

### Advantages

- Removes oil and grease accumulations
- Pleasant citrus odor
- Concentrated for economy and ease of use
- USDA authorized

### Suitable Substrates

- Existing Concrete

### Packaging

5 Gal (18.9 L)

### Approximate Coverage

Cleaning Agent: 150 ft<sup>2</sup>/gal (3.7 m<sup>2</sup>/L) (Diluted)

### Shelf Life

Keep in tightly sealed containers and stored between 50°F and 90°F (10°-35°C). Shelf life is twelve (12) months in original, unopened containers

### Limitations

- Do not use on resilient tile, rubber or asphalt, and painted wall surfaces
- Do not use in the presence of open foodstuffs
- Remove food before using
- For commercial and industrial use only

### Cautions

- CITREX contains citrus terpenes
- Wear protective gloves and goggles
- Do not use on rubber, resilient tiles, or asphalt surfaces
- Do not use near fire or flame
- Harmful if swallowed
- Do not use in presence of open foodstuffs
- For industrial use only by trained personnel
- Please refer to Safety Data Sheet (SDS) before using
- Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting,

abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

#### 4. TECHNICAL DATA



#### Physical Properties

Property	Observed
Color	Amber
Odor	Orange
Phosphate	None
Film	None
USDA approved	Yes
pH 5% emulsion	6-7

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### 5. INSTALLATION

**As a cleaner:** For general cleanup applications, dilute CITREX™ with water to suit the extent of the accumulated dirt. A solution of 1 part CITREX to 5 parts water is usually adequate for most cleaning jobs. Experiment with varied concentrations to determine which strength is most suitable for the cleaning and degreasing task. Add a minimum of 15 oz/gal (117 ml/L). This cleaner may be applied using automatic floor scrubbers, sprayers or conventional methods. Heavily caked grease should be first scraped from surfaces. Apply diluted CITREX at the rate of 150 ft<sup>2</sup>/gal (3.7m<sup>2</sup>/l).

**Application:** Allow to stand 2-10 minutes. Scrub contaminated area. Flush with water or vacuum loosened contaminants, dirt, oil and grease after scrubbing. Redo areas where heavy accumulation of tire marks, sealer film, oil, grease or other contaminants has occurred and some stubborn stains remain.

#### 6. AVAILABILITY AND COST

##### Availability

LATICRETE materials are available worldwide.

#### For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [laticrete.com](http://laticrete.com)

#### Cost

Contact a LATICRETE Distributor in your area.

#### 7. WARRANTY

See 10. FILING SYSTEM:

#### 9. TECHNICAL SERVICES

##### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

##### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

#### 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2022 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.