



# STONETECH® Polishing Powder

DS-224.5-0120

**Globally Proven  
Construction Solutions**



## Suitable Substrates

- Marble
- Limestone
- Travertine
- Terrazzo

## Packaging US and CANADA

- ST326-0625: 1lb 9oz (708G) Canister - 6 / Case

## 1. PRODUCT NAME

STONETECH® Polishing Powder

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

STONETECH® Polishing Powder is the stone restoration powder that eliminates etch marks and light wear patterns and creates a smooth, satin finish. This non-acidic powder is designed for professional use on natural stone and terrazzo surfaces. Recommended for use following STONETECH honing powders to produce a natural polished finish.

### Uses

- Countertops
- Backsplashes
- Floors
- Walls

### Advantages

- Creates a smooth, satin finish
- Eliminates etch marks and light wear patterns
- Non-acidic for natural stone
- Designed for professional use

## Approximate Coverage

- Up to 1000 ft<sup>2</sup> per lb (205 m<sup>2</sup>/kg), depending on the porosity of the surface

## Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

## Cautions

- Inhalation: Remove victim to fresh air. Get medical attention if symptoms persist.
- Skin contact: Wash area with soap and water. Get medical attention if irritation develops or persists.
- Eye contact: Do not rub eyes. Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists.
- Ingestion: Rinse mouth and drink plenty of water. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort occurs.

## 4. TECHNICAL DATA



### Physical Properties

Form	Powder
Color	White
Odor	none
Specific Gravity	3.6

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, dry and free of waxes and coatings.

### Directions

1. If surface is heavily soiled, pre-clean with STONETECH® KlenzAll™ Cleaner if needed.
2. Mask off and protect any baseboards or adjacent areas to avoid splashing and overspray onto surfaces not intended to be treated.
3. If STONETECH Polishing Powder is used following the use of STONETECH Honing Powder, ensure that the surface is well rinsed and a new pad is used.
4. Apply approximately 1/2 cup (113 g) STONETECH Polishing Powder and 1 cup (237 ml) of clean water to stone surface.
5. Refinish using a hand orbital sander or weighted floor machine at 130-140 lbs (59 – 64 kg), 175 rpm, fitted with a natural hair pad.
6. Keep compound wet while refinishing with plenty of water. Add STONETECH Polishing Powder as needed.
7. Refinish area until the desired level of polish has been achieved.
8. Rinse well and use a wet vacuum or hot water extraction unit to remove all remaining compound.

## 6. AVAILABILITY AND COST

### Availability

LATICRETE materials are available worldwide.

### For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [laticrete.com](http://laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

- DS.230.13: 1 Year Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, and/or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, and a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- DS 215.0: STONETECH KlenzAll Cleaner
- TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.