



STONETECH® BulletProof® Sealer

DS-282-1119

**Globally Proven
Construction Solutions**



Advantages

- Offers maximum stain protection
- Best protection for the most porous natural stone, tile, masonry and grout
- Preserves the original look of the surface
- Water-based formula is better for you and the environment
- For interior and exterior use
- Professional grade

Suitable Substrates

- Granite
- Marble
- Quartzite
- Limestone
- Travertine
- Sandstone
- Saltillo
- Bluestone
- Flagstone
- Basalt
- Grout

Packaging US

- ST302-1202: 2oz (59ML) Sample Bottle - 12 / case - NOT For Resale
- ST302-1216: Pint /16oz (473ML) Bottle - 12 / case
- ST302-0632: Quart / 32oz (946ML) Bottle - 6 / case
- ST302-0401: Gallon / 128oz (3.8L) Bottle - 4 / case
- ST302-0105: 5 Gallon (18.9L) Drum - 1 unit
- *ST302-0155: 55 Gallon (208L) Drum - 1 unit

CANADA

- ST345-1216: Pint /16oz (473ML) Bottle - 12 / case
- ST345-0632: Quart / 32oz (946ML) Bottle - 6 / case
- ST345-0401: Gallon / 128oz (3.8L) Bottle - 4 / case
- ST345-0105: 5 Gallon (18.9L) Drum - 1 unit

*Make to order. See Sales Representative for Approval.

1. PRODUCT NAME

STONETECH® BulletProof® Sealer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

STONETECH BulletProof® Sealer is the premium, water-based penetrating sealer, designed to provide maximum stain protection against the toughest oil and water-based stains. This professional grade sealer effectively impregnates into the most porous natural stone, tile, masonry and grout surfaces in interior and exterior applications and does not alter the natural look of the surface. A high performing, safer alternative to solvent based sealers, STONETECH BulletProof Sealer is better for you and the environment and comes with a lifetime product guarantee.

Great for use in high traffic areas such as countertops, back splashes, entryways, floors and walls.

Uses

- Countertops
- Backsplashes
- Floors
- Walls

Approximate Coverage

- Up to 112 ft²/pint (10.4 m²/473 mL) / single coat
- Up to 225 ft²/quart (21.9 m²/946 mL) / single coat
- Up to 900 ft²/gallon (83.6 m²/3.8 L) / single coat
- Up to 4500 ft²/ 5 gallon (418 m²/18.9 L) / single coat
- Up to 49,500 ft²/55 gallon (4,599 m²/208L) / single coat

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures <50°F (10°C) and >90°F (32°C).

Cautions

Consult SDS for more safety information.

- Inhalation: In high concentrations, vapors may be irritating to the respiratory system
- Skin contact: May cause skin irritation
- Eye contact: May cause eye irritation
- Ingestion: May cause discomfort if swallowed

Storage and Handling Instructions: Avoid prolonged exposure to vapors. Use in a well-ventilated area. Do not ingest. Avoid contact with eyes and skin. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

4. TECHNICAL DATA



VOC/LEED Product Information

<400 g/L (excluding water) for EPA Purposes
<20 g/L (including water) for LEED and U.S. State purposes (Low Solids Coating)

Physical Properties

Form	Liquid
Color	Pale Amber
Odor	Mild
pH	9 – 11
Specific Gravity	1.009

Working Properties

Full Cure	24 – 72 hours
Surface Traffic	6 – 8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures

used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24 hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean and free of waxes and coatings. Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F (10°C and 26°C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

Directions

1. Ensure cap is closed and sealed, and shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally apply an even coat of STONETECH® BulletProof Sealer using a paint pad, roller, brush or low-pressure sprayer.
4. Allow sealer to penetrate the surface for 10-15 minutes. During this time, keep the surface wet with sealer, adding more sealer as needed. DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.
5. Thoroughly wipe dry the entire surface with clean absorbent towels.
6. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied within 30-40 minutes from the initial application as directed in steps 3-5.
7. Should a sealer residue appear, rewet the impacted section of the surface with sealer. Agitate the surface with a white nylon scrubbing pad to loosen residue and wipe dry with a clean, absorbent towel.
8. A full cure is achieved in 24-72 hours. Use of the treated surface may resume in 6-8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
9. Clean tools used during application with water.

Expected Wear

- Up to 5 years on interior surfaces
 - Up to 3 years on exterior surfaces
- For best results, reapply annually.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

laticrete.com**Cost**

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- DS-230.30ST: Lifetime LATICRETE STONETECH Product Warranty (English)

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the STONETECH sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide Guide.

9. TECHNICAL SERVICES**Technical Assistance**

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety LiteratureTo acquire technical and safety literature, please visit our website at laticrete.com.**10. FILING SYSTEM**Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.30ST - LATICRETE® Product Warranty
- STONETECH Countertop Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- DS 215.0: STONETECH KlenzAll™ Cleaner
- TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2019 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.