



# PERMAGUARD Traction Additive

DS-36608-0220

**Globally Proven  
Construction Solutions**



- Preserves clarity of topcoat
- Lightweight

### Suitable Substrates

- Epoxy Coating

### Packaging

Traction Additive: 16 fl.oz. (473 mL) pouch

### Approximate Coverage

See applicable coating data sheet for coverage rates.

### Shelf Life

Unlimited. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun).

### Limitations

- Follow temperature guidelines for specific PERMAGUARD coating being used.

### Cautions

- Thoroughly read all technical data sheets, application guidelines, warranty disclaimers and Safety Data Sheets (SDS) prior to use. Visit [permaguardgaragecoatings.com](http://permaguardgaragecoatings.com) for additional installation videos, FAQs and tips.
- Wear protective gloves, protective clothing and eye protection.
- Keep out of reach of children.
- Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use.

## 4. TECHNICAL DATA

### VOC/LEED Product Information

0 g/L

## 1. PRODUCT NAME

PERMAGUARD Traction Additive

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Toll Free: 1.800.451.1111  
Fax: +1.203.393.1684  
Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

PERMAGUARD Traction Additive is an ultra-durable, high strength traction additive designed for use in clear and pigmented PERMAGUARD flooring system.

### Available Products:

- 9832-0016-1 PERMAGUARD Traction Additive

### Uses

- Garage Floors
- Basement Floors
- Workshop Floors
- Utility Room Floors
- Light Duty Flooring

### Advantages

- Improves surface traction
- Tough & durable

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Mixing / Application

Thoroughly mix coating per manufactures instructions prior to adding PERMAGUARD Traction Additive. Once mixed, add 6-8 fl.oz. (177-237 mL) by volume of PERMAGUARD Traction Additive per mixed gallon. Mix for an additional 1-2 minutes or until the product is uniformly dispersed. Mix intermittently during use to ensure settling does not occur. For extra traction, increase the amount of PERMAGUARD Traction Additive used.

## 6. AVAILABILITY

### Availability

LATICRETE materials are available worldwide. For on-line distributor information, visit LATICRETE at [www.laticrete.com](http://www.laticrete.com)

## 7. WARRANTY

See 10. FILING SYSTEM:

- DS 230.13: 1 Year Product Warranty

## 8. MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependent upon a good routine maintenance program. PERMAGUARD floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent sweeping of debris from the surface and thorough cleaning utilizing a neutral pH cleaner (i.e. STONETECH Stone & Tile Cleaner). Frequency of sweeping and washing will vary depending on floor usage type, traffic and age.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the Technical Service Hotline:

1-800-368-5272  
Toll Free: 1.800.368.5272  
Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.laticrete.com](http://www.laticrete.com). The following is a list of documents:

- DS 36605: PERMAGUARD MAX
- DS 36606: PERMAGURAD MAX Topcoat
- DS 36602: PERMAGUARD Plus
- DS 36604: PERMAGUARD Plus Topcoat

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.