



SPARTACOTE™ METALLIC PIGMENT™

DS-085.7-0217

A product brand of LATICRETE International, Inc.



Uses:

- Decorative flooring for retail stores
- Car dealerships
- Residential flooring
- Stadium Flooring

Packaging

8 oz (227 g) Jar
32 oz (908 g) Jar

Approximate Coverage

8 oz (227 g)/gal (3.8 L), 100 ft²/gal (2.4 m²/L)

Shelf Life

One year unopened

Cautions

FOR PROFESSIONAL USE ONLY

- Thoroughly read all technical data sheets, application guidelines, warranty disclaimers and Safety Data Sheets (SDS) prior to use. Application guides depending on the dye system employed are available at www.laticrete.com.
- Polyaspartic aliphatic polyurea products contain chemical ingredients that are considered hazardous. Read the container label warning and SDS prior to use.
- Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 Minutes, if symptoms persist seek medical attention.

Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

4. TECHNICAL DATA

Working Properties

Specifications are subject to change without notification. Technical data shown in product data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary due to critical job site factors. All recommendations, statements and technical data contained in this data sheet are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind. Satisfactory results depend upon many factors beyond the control of LATICRETE International, Inc. User shall rely on their own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from their direct use, indirect use or consequential to their use of the product. LATICRETE shall not be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use or inability to use the product.

1. PRODUCT NAME

SPARTACOTE™ METALLIC PIGMENT™

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: 1.866.966.1329

Toll Free Fax: 1.855.683.7257

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

SPARTACOTE METALLIC PIGMENTS are composed of specialized aluminum prism pigments which are available in a powder form. These pigments are dispersed into SPARTACOTE™ FLEX SB™ polyaspartic coatings to create a remarkably iridescent effects with extraordinary color variety and depth. These flooring systems provide architects and designers with the ability to create customized decorative flooring finishes with the enhanced durability necessary for heavy traffic environments.

Advantages

- Customizable finishes
- 12 Colors
- 3 coat process
- Low maintenance
- High reflectivity
- Suitable for any environment
- Provides incredible depth and radiance

5. INSTALLATION

Please consult the SPARTACOTE™ System Application Guide.

6. AVAILABILITY AND COST

Availability

SPARTACOTE and LATICRETE® materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.laticrete.com.

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

DS 200.03: LATICRETE 3 Year Decorative Finish
System Warranty

8. MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependence upon a good routine maintenance program designed specifically for the installed wear surface. SPARTACOTE polyaspartic and epoxy floor coating systems are nonporous, causing dirt and contaminants to remain on the surface. The use of properly placed walk-off mats, inside and outside, will help increase the life of the floor. Recommend maintenance program consist on frequent and through cleaning utilizing a neutral pH cleaner (e.g. Simple Green®). Frequency of washing will vary depending on floor usage type, traffic and age.

Please Refer to TDS 420 "SPARTACOTE Floor Maintenance Guide" available at www.laticrete.com for more information.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.866.966.1329

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at www.laticrete.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 200.03: LATICRETE 3 Year Decorative Finish
System Warranty

DS 086.4: SPARTACOTE FLEX SB™

TDS 420: SPARTACOTE Floor Maintenance Guide

©2016 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.

HP SPARTACOTE

A product brand of LATICRETE International, Inc.

LATICRETE International, Inc. ■ One LATICRETE Park North, Bethany, CT 06524-3423 USA ■ 1.800.243.4788 ■ +1.203.393.0010 ■ www.laticrete.com