



STONETECH® Polishing Powder

DS 224.5-0616

**Globally Proven
Construction Solutions**



Item Numbers and Packaging

D12447164 – 1lb 9oz (708g) Canister, 6 units per Case, 100 units per Pallet

D12612379 – 10lb (4.5kg) Bucket, 1 units per Case

Approximate Coverage

- Up to 1000 ft² per lb (205 m²/kg), depending on the porosity of the surface

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

Storage and Handling Instructions

CAUTION: MAY CAUSE MILD EYE AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid inhalation of dust. KEEP OUT OF THE REACH OF CHILDREN.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air. Get medical attention if symptoms persist.
- Skin contact: Wash area with soap and water. Get medical attention if irritation develops or persists.
- Eye contact: Do not rub eyes. Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists.
- Ingestion: Rinse mouth and drink plenty of water. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort occurs.

4. TECHNICAL DATA

Physical Properties

Form	Powder
Color	White
Odor	none
Specific Gravity	3.6

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, dry and free of waxes and coatings.

1. PRODUCT NAME

STONETECH® Polishing Powder

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

STONETECH Polishing Powder produces a natural polished finish.

Uses

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Creates smooth, satin finish
- Eliminates etch marks and light wear patterns
- Non-acidic
- Designed for professional use

Recommended Surfaces:

Natural stone such as most:

- Marble
- Limestone
- Travertine
- Terrazzo

Directions

1. If surface is heavily soiled, pre-clean with STONETECH® KlenzAll™ Cleaner if needed.
2. Mask off and protect any baseboards or adjacent areas to avoid splashing and overspray onto surfaces not intended to be treated.
3. If STONETECH Polishing Powder is used following the use of STONETECH Honing Powder, ensure that the surface is well rinsed and a new pad is used.
4. Apply approximately 1/2 cup (113 g) STONETECH Polishing Powder and 1 cup (237 ml) of clean water to stone surface.
5. Refinish using a hand orbital sander or weighted floor machine at 130-140 lbs (59 – 64 kg), 175 rpm, fitted with a natural hair pad.
6. Keep compound wet while refinishing with plenty of water. Add STONETECH Polishing Powder as needed.
7. Refinish area until the desired level of polish has been achieved.
8. Rinse well and use a wet vacuum or hot water extraction unit to remove all remaining compound.

6. AVAILABILITY AND COST

Availability

LATICRETE, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, and/or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll Cleaner, and a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service

Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13:	LATICRETE Product Warranty
DS 211.0:	STONETECH Stone & Tile Cleaner
DS 215.0:	STONETECH KlenzAll Cleaner
TDS 262:	Stone and Tile Care Guide