



Premium Stone Sealer

DS 377.0-0516

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATICRETE® Premium Stone Sealer

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA
Telephone: +1.203.393.0010
Toll Free: +1.888.786.6343
Fax: +1.203.393.1684
Website: www.laticrete.com

3. PRODUCT DESCRIPTION

LATICRETE® Premium Stone Sealer is an advanced sealer, designed to provide maximum protection on natural stone against the toughest oil, food, and water-based stains while preserving the stone's natural color and shine. Intended for use in heavy traffic and heavy use areas.

Uses (Interior and Exterior Use)

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Maximum protection against oil, food, and water-based stains
- Protects heavy use and heavy traffic areas
- Water-based formula
- Interior and exterior use

Recommended Surfaces:

Natural stone and Masonry Surfaces such as:

- Granite
- Marble
- Quartzite
- Travertine

- Slate
- Limestone
- Saltillo Tile
- Bluestone
- Sandstone
- Flagstone

Item Numbers and Packaging

D14924471 – Gallon (3.8 L), 4 units per Case, 160 units per Pallet
D14924497 – Quart 32oz (946 mL), 4 units per Case, 640 units per Pallet

Approximate Coverage

Up to 125 ft²/quart (11.6 m²/946 ml) for a two-coat application
Up to 500 ft²/gallon unit (46.3 m²/3.8 L) for a two-coat application

Expected Wear

- Up to 5 years on interior surfaces
- Up to 3 years on exterior surfaces

For best results, reapply annually

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

<235 g/L (excluding water) For EPA purposes
<5 g/L (including water) Low Solids Coating

Storage and Handling Instructions

Avoid prolonged exposure to vapors. Use only in a well-ventilated area. Do not ingest. Avoid contact with eyes and skin. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

Cautions

Consult SDS for more safety information.

- Ingestion: Rinse mouth. Do not induce vomiting. Seek medical attention if any discomfort continues.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	Pale Amber
Odor	Mild
pH	9 – 11

Working Properties

Full Cure	24 – 72 hours
Surface Use	6 – 8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24 hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean and free of waxes and coatings. LATICRETE® Premium Stone Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F (10°C and 26°C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

Directions

1. Ensure cap is closed and sealed; shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally apply an even coat of LATICRETE® Premium Stone Sealer using a paint pad, roller, brush or low-pressure sprayer.
4. Allow sealer to penetrate the surface for 10 – 15 minutes. During this time, keep the surface wet with sealer, adding more sealer as needed. **DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.**
5. Thoroughly wipe dry the entire surface with clean, absorbent towels.
6. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied 30 – 40 minutes after the initial application as directed in steps 3 – 5.
7. Should a sealer residue appear, rewet the impacted section of the surface with sealer. Agitate the surface with a white nylon scrubbing pad to loosen residue and wipe dry with a clean, absorbent towel.
8. A full cure is achieved in 24 – 72 hours. Use of the treated surface may resume in 6 – 8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
9. Clean tools used during application with water.

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty
STONETECH WARRANTY

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as LATICRETE® Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use LATICRETE® Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE® Product Warranty

DS 370.5: LATICRETE® Stone & Tile Floor Cleaner

DS 372.5: LATICRETE® Heavy Duty Tile & Grout Cleaner