



Aerosol Grout Sealer

DS 378.0-0516

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATICRETE® Aerosol Grout Sealer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

LATICRETE® Aerosol Grout Sealer is a quick and easy to use grout sealer which helps keep cement based grout looking new.

Uses (Interior and Exterior)

- Countertops
- Backsplashes
- Floors
- Walls

Advantages

- Protection against water and oil-based stains
- Continuous flow spray allows for wall-to-floor application
- Penetrating formula seals out moisture
- Interior and exterior use

Recommended Surfaces

Cement-based grout for natural stone, ceramic and porcelain tile.

Item Numbers and Packaging

D14924063 – 13.5 oz Aerosol Can (399 ml), 6 units per Case, 960 units per Pallet

Approximate Coverage

- Up to 125 linear ft/ 13.5 oz Can (38.1 linear m/ 399 ml)

Expected Wear

- Up to 5 years on interior surfaces
- Up to 3 years on exterior surfaces

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

PWMIR<1.50g O3/g product (Clear Coatings)

Storage and Handling Instructions

DANGER! EXTREMELY FLAMMABLE. Contains naphtha (petroleum), hydrotreated heavy (CAS# 64742-48-9), and propane (CAS# 74-98-6) and butane (CAS# 106-97-8) as propellants. Do not use near sources of ignition, heat, flame, spark, or live electrical equipment, or while smoking. Vapors can travel to distant ignition sources. **VAPOR HARMFUL.** Do not breathe vapors or spray mist. **USE ONLY IN A WELL-VENTILATED AREA.** If unsure whether area is well-ventilated, use NIOSH approved respirator with a combination HEPA/organic vapor cartridge. Prevent build-up of vapors by opening windows and doors and by using exhaust fans. Intentional misuse by deliberately inhaling contents of this container may be **HARMFUL OR FATAL. HARMFUL OR FATAL IF SWALLOWED.** Do not ingest. **MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.** Avoid eye and skin contact. For safest application, wear protective eyewear, gloves, long sleeves, and long pants. **CONTENTS UNDER PRESSURE.** Do not puncture, incinerate, or store above 120°F (49°C). Exposure to heat or prolonged exposure to sunlight may cause bursting. Do not discard can in trash compactor or burn. Do not mix product with other chemicals. Rags, clothing, and other equipment wet with product may be combustible. Clean up promptly after job is complete. Remove any clothing that comes in contact with product. Allow rags and clothing to dry in well ventilated area away from children and pets. When dry, dispose of rags. Wash affected clothing before re-wearing. **KEEP OUT OF THE REACH OF CHILDREN.** For professional or frequent use, a NIOSH-approved respirator with a HEPA/organic vapor cartridge is recommended. Consult product MSDS.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove person to fresh air immediately. Call a physician if respiratory irritation, nausea, or dizziness persists.
- Skin contact: Wash skin with soap and water. Get medical attention if irritation develops and persists.

- Eye contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
- Ingestion: Immediately rinse mouth and drink plenty of water. Do not induce vomiting. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.

4. TECHNICAL DATA

Physical Properties

Form	Aerosol Liquid
Color	Clear
Odor	Solvent

Working Properties

Full Cure	24 – 48 hours
Surface Use	6 – 8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Ensure area is well-ventilated during application and until surface is dry. Open windows and doors and use exhaust fans. Surface temperature should be 50°F – 80°F (10°C - 26°C). Keep children and pets out of area until treated surfaces are dry. Always test in a small inconspicuous area to determine appropriate application method and desired results. Avoid spraying surfaces not intended for treatment. Can be used 24 hours after grouting. Grout should be firm to the touch before application, grout must be clean, dry, and free of sealers and coatings.

Directions

1. Shake well before using.
2. Hold can with extended arm 10" to 16" (254 – 406 mm) from the grout surface, aim nozzle, and spray LATICRETE® Aerosol Grout Sealer evenly along the grout line. Keep can tilted to assure even product distribution.
3. After 10 to 15 minutes, wipe entire surface with dry cloth to remove excess sealer.
4. Dried residue from excess sealer can be removed from tile surfaces by wiping with a dry cloth.
5. A second coat is recommended and may be applied as soon as one hour after completing initial application.
6. Surface traffic may begin 2 hours after final application. It is required to keep the installation dry for a minimum of 12 hours, optimally 36 – 72 hours.

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as LATICRETE Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use LATICRETE Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 370.5: LATICRETE Stone & Tile Floor Cleaner

DS 372.5: LATICRETE Heavy Duty Tile & Grout Cleaner