



# LATICRETE® Semi Gloss Sealer & Finish

DS 380.5-0616

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

LATICRETE® Semi Gloss Sealer & Finish

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010  
Toll Free: +1.888.786.6343  
Fax: +1.203.393.1684  
Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

LATICRETE® Semi Gloss Sealer & Finish is an easy-to-use, two-in-one formula that leaves a light sheen while protecting against stains. It is designed to deepen and enhance the stone's natural color.

### Uses (Interior only)

- Floors
- Walls
- Backsplashes

### Advantages

- Two-in-one formula provides a light sheen and stain protection
- Deepens and enhances natural color
- Easy-to-use, water-based formula
- Provides protective finish against stains

### Recommended Surfaces

Natural stone and masonry surfaces such as:

- Slate
- Saltillo Tile
- Textured limestone
- Textured travertine
- Concrete

Not intended for use on glazed, polished, honed or non-absorbing surfaces, showers, countertops or near pool areas, wood floors & decks.

### Item Numbers and Packaging

D14924669 – Quart 32oz (946 mL) Container, 4 units per Case, 640 units per Pallet

### Approximate Coverage

- Up to 75 ft<sup>2</sup> per quart container (7 m<sup>2</sup> per 946 mL), depending on porosity of the surface being treated
- Up to 300 ft<sup>2</sup> per gallon container (27.8 m<sup>2</sup> per 3.8 L), depending on porosity of the surface being treated

### Expected Wear

Up to 5 years. Touch up on higher traffic areas may be required on a more frequent basis.

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

<55 g/L (excluding water)

### Storage and Handling Instructions

CAUTION: MAY CAUSE RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. For repeated or professional use, an approved respirator and gloves are recommended. Consult SDS. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

### Cautions

Consult SDS for more safety information.

- Inhalation: Remove affected person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if discomfort continues.
- Ingestion: Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention.

## 4. TECHNICAL DATA

### Physical Properties

Form	Liquid
Color	Opaque, White
Odor	Slight, Acrylic-Like

### Working Properties

Full Cure	24 – 48 hours
Surface Use	12 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine appropriate application method, achievement of desired results, and to ensure good adhesion. Surface must be thoroughly clean, dry, and free of any sealers or coatings before application. To remove old, worn finishes or sealers, use LATICRETE® Heavy Duty Coating Stripper. Application to a dirty or dusty surface will affect adhesion and appearance. Avoid applying in direct sunlight, surface temperature should be 50°F – 80°F (10°C – 26°C). LATICRETE® Semi Gloss Sealer & Finish should not be applied to a wet or moist surface. Avoid applying onto surfaces not intended for treatment. For new installations with grout, sealer can be applied as soon as 48 – 72 hours after grouting. Fresh concrete slabs require a minimum of 28 days to cure before applying the sealer. Keep children and pets out of the area until surface traffic resumes.

### Directions

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Liberally apply 1 – 3 even coats of LATICRETE® Semi Gloss Sealer & Finish with a natural bristle paint brush, paint roller, low pressure sprayer, or pump-up garden sprayer. Avoid puddling of product during application.
3. Allow 30 – 45 minutes between coats or until the surface is dry.
4. Surface traffic may begin 12 hours after final application; keep installation dry for a minimum of 12 hours; full cure is achieved in 24 – 48 hours.
5. Keep surfaces clean and dry as finished surfaces may become slippery when wet.
6. Clean tools used during application immediately with water.

## 6. AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

### For Distributor Information, Call:

Toll Free: +1.888.786.6343  
Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [www.stonetech.com](http://www.stonetech.com) or [www.laticrete.com](http://www.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as LATICRETE® Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use LATICRETE® Heavy Duty Tile & Grout Cleaner with a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2  
Telephone: +1.203.393.0010, ext. 235  
Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com) or [www.stonetech.com](http://www.stonetech.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.stonetech.com](http://www.stonetech.com). The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty  
DS 370.5: LATICRETE® Stone & Tile Floor Cleaner  
DS 372.5: LATICRETE® Heavy Duty Tile & Grout Cleaner  
DS 373.0: LATICRETE® Heavy Duty Coating Stripper