



LATICRETE® High Gloss Sealer & Finish

DS 381.0-0616

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATICRETE® High Gloss Sealer & Finish

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

LATICRETE® High Gloss Sealer & Finish is a high performance sealer that provides a high gloss shine while deepening and enhancing the stone's natural color. It provides a protective finish against future stains.

Uses (Interior only)

- Floors
- Walls

Advantages

- Provide protection against stains
- Provides high gloss, wet-look shine
- Deepens and enhances color
- Easy-to-use, water based formula

Recommended Surfaces

Natural stone and masonry surfaces such as:

- Slate
- Saltillo tile
- Textured limestone
- Textured travertine
- Concrete

Not intended for use on glazed, polished, honed or non-absorbing surfaces, showers, countertops or near pool areas, wood floors and decks.

Item Numbers and Packaging

D15134833 – Quart 32oz (946 mL) Container, 4 units per Case, 640 units per Pallet

Approximate Coverage

- Up to 75 ft² / 32oz (7 m²/ 946 mL), depending on porosity of the surface
- Up to 300 ft² / gallon (27.8 m²/ 3.8 L), depending on porosity of the surface

Expected Wear

Up to 5 years. Touch ups on higher traffic areas may be required on a more frequent basis.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

<85 g/L (excluding water)

Storage and Handling Instructions

CAUTION: MAY CAUSE RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. For repeated or professional use, an approved respirator and gloves are recommended. Consult SDS. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

Cautions

Consult SDS for more safety information.

- Inhalation: Remove affected person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if any discomfort persists.
- Ingestion: Rinse mouth. Do not induce vomiting. Seek medical attention if any discomfort continues.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	White
Odor	Slightly Acrylic-Like
pH	8.7

Working Properties

Full Cure	24 – 48 hours
Surface Use	12 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine appropriate application method, achievement of desired results, and to ensure good adhesion. Surface must be thoroughly clean, dry, and free of any sealers or coatings before application. To remove old, worn finishes or sealers, use LATICRETE® Heavy Duty Coating Stripper. Application to a dirty or dusty surface will affect adhesion and appearance. Avoid applying in direct sunlight, surface temperature should be 50°F – 80°F (10°C – 26°C). LATICRETE® High Gloss Sealer & Finish should not be applied to a wet or moist surface. Avoid applying onto surfaces not intended for treatment. For new installations with grout, sealer can be applied as soon as 72 hours after grouting. Fresh concrete slabs require a minimum of 28 days to cure before applying the sealer. Keep children and pets out of the area until surface traffic resumes.

Directions

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Mark off surfaces not intended to be treated
3. Liberally apply 1 – 3 even coats of LATICRETE® High Gloss Finishing Sealer and finish with a natural bristle paint brush, paint roller, low pressure sprayer, or pump-up garden sprayer. Avoid puddling of product during application.
4. Allow 30 – 45 minutes between coats or until the surface is dry.
5. Surface traffic may begin 12 hours after final application; keep installation dry for a minimum of 12 hours; full cure is achieved in 24 – 48 hours.
6. Keep surfaces clean and dry as finished surfaces may become slippery when wet.
7. Clean tools used during application immediately with water.

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH®, and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343
Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer

used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2
Telephone: +1.203.393.0010, ext. 235
Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty
DS 370.5: LATICRETE® Stone & Tile Floor Cleaner
DS 372.5: LATICRETE® Heavy Duty Tile & Grout Cleaner
DS 373.0: LATICRETE® Heavy Duty Coating Stripper