

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE NXT Skim

Other means of identificationNot available.Recommended usePatching.Recommended restrictionsNone known.

Manufacturer / Importer / Supplier / Distributor information

Company Name
 LATICRETE International
 1 Laticrete Park, N
 Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Reproductive toxicity Category 1B

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

damage fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be

allowed out of the workplace.

Response If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If

skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	35-45
Calcium aluminate cement	65997-16-2	20-30
Calcium sulfate hemihydrate	26499-65-0	6-12

LATICRETE NXT Skim SDS US

917237 Version #: 01 Revision date: - Issue date: 11-November-2013

Portland Cement	65997-15-1	4-6
Cellulose	9004-34-6	0.5-1.5
Lithium Carbonate	554-13-2	0.1-0.25

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

cause chronic effects.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

None known

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery,

flush area with water.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium sulfate hemihydrat e (CAS 26499-65-0)	PEL	5 mg/m3	Respirable fraction.
·		15 mg/m3	Total dust.
Cellulose (CAS 9004-34-6)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
·		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910	.1000)		
Components	Туре	Value	
Portland Cement (CAS 65997-15-1)	TWA	50 millions of particle	
,		particie	
US. ACGIH Threshold Limit Values	5		
Components	Туре	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Туре	Value	Form	
Calcium sulfate hemihydrat e (CAS 26499-65-0)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Cellulose (CAS 9004-34-6)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.	
		10 mg/m3	Total	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.	
,		10 mg/m3	Total	

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear chemical-resistant, impervious gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protectionWear a dust mask if dust is generated above exposure limits. **Thermal hazards**Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder.
Color Gray.
Odorless.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not flammable or combustible. Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Not available.

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

Vapor pressure Not available. Not available. Vapor density

1.25 Relative density Solubility(ies) Insoluble

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Swallowing may cause gastrointestinal irritation. Ingestion

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation Skin contact

Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components **Species Test Results** Lithium Carbonate (CAS 554-13-2)

Acute

Inhalation

LC50 Rat > 2.17 mg/l, 4 Hours

Oral

LD50 Rat 525 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

No data available. Respiratory sensitization

LATICRETE NXT Skim SDS US 4/7

917237 Version #: 01 Revision date: -Issue date: 11-November-2013 **Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not available.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases

Further information No other specific acute or chronic health impact noted.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components Species Test Results

Calcium sulfate hemihydrate (CAS 26499-65-0)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Lithium Carbonate (CAS 554-13-2)

Aquatic

Fish LC50 Mummichog (Fundulus heteroclitus) 8.1 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil The product is not mobile in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Administration (FDA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer

and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Calcium sulfate hemihydrate (CAS 26499-65-0)

Cellulose (CAS 9004-34-6) Limestone (CAS 1317-65-3) Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1)

US. New Jersey Worker and Community Right-to-Know Act

Lithium Carbonate (CAS 554-13-2) 500 lbs

US. Pennsylvania RTK - Hazardous Substances

Calcium sulfate hemihydrate (CAS 26499-65-0)

Cellulose (CAS 9004-34-6) Limestone (CAS 1317-65-3) Portland Cement (CAS 65997-15-1)

US. Rhode Island RTK

Lithium Carbonate (CAS 554-13-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lithium Carbonate (CAS 554-13-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\/--

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 11-November-2013

Revision date - Version # 01

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE NXT Skim SDS US

917237 Version #: 01 Revision date: - Issue date: 11-November-2013