# LATICRETE

# **SAFETY DATA SHEET**

#### 1. Identification

Product identifier DRYTEK® Levelex® DL

Other means of identification None.

**Recommended use** Decorative Topping.

**Recommended restrictions** Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company Name LATICRETE International

Address 1 Laticrete Park, N

Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation

Category 1

Carcinogenicity

Category 1

Category 1

Category 1A

Reproductive toxicity

Category 1B

Specific target organ toxicity, repeated

Category 2 (lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May damage fertility or the unborn child. May cause damage to organs (lung)

through prolonged or repeated exposure.

**Precautionary statement** 

**Prevention**Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume. Wash thoroughly after handling. Wear protective

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be

allowed out of the workplace.

Response If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. If

skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

DRYTEK Levelex DL SDS US

917568 Version #: 02 Revision date: 08-August-2016 Issue date: 05-June-2014

**Storage** Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

Not classified.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name               | CAS number | %         |  |
|-----------------------------|------------|-----------|--|
| Silica Sand                 | 14808-60-7 | 40-50     |  |
| Calcium aluminate cement    | 65997-16-2 | 12-18     |  |
| Calcium sulfate dihydrate   | 13397-24-5 | 6 - 10    |  |
| Portland Cement             | 65997-15-1 | 1-3       |  |
| Titanium dioxide            | 13463-67-7 | 0.5-2     |  |
| Calcium sulfate hemihydrate | 10034-76-1 | 0.8 - 1   |  |
| Lithium Carbonate           | 554-13-2   | 0.07-0.15 |  |

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical Skin contact

advice/attention. Take off contaminated clothing and wash before reuse.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed **General information**  Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated

clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

DRYTEK Levelex DL SDS US Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components   | Туре                                | Value                  | Form                        |
|--|-------------------------------------|------------------------|-----------------------------|
| Calcium sulfate dihydrate (CAS 13397-24-5)         | PEL                                 | 5 mg/m3                | Respirable fraction.        |
|  |                                     | 15 mg/m3               | Total dust.                 |
| Portland Cement (CAS 65997-15-1)                   | PEL                                 | 5 mg/m3                | Respirable fraction.        |
|  |                                     | 15 mg/m3               | Total dust.                 |
| Titanium dioxide (CAS 13463-67-7)                  | PEL                                 | 15 mg/m3               | Total dust.                 |
| US. OSHA Table Z-3 (29 Cl                          | FR 1910.1000)                       |                        |                             |
| Components   | Туре                                | Value                  | Form                        |
| Portland Cement (CAS 65997-15-1)                   | TWA                                 | 50 mppcf               |                             |
| Silica Sand (CAS<br>14808-60-7)                    | TWA                                 | 0.3 mg/m3              | Total dust.                 |
|  |                                     | 0.1 mg/m3              | Respirable.                 |
|  |                                     | 2.4 mppcf              | Respirable.                 |
| US. ACGIH Threshold Lim                            | it Values                           |                        |                             |
| Components   | Туре                                | Value                  | Form                        |
| Calcium sulfate dihydrate (CAS 13397-24-5)         | TWA                                 | 10 mg/m3               | Inhalable fraction.         |
| Calcium sulfate<br>hemihydrate (CAS<br>10034-76-1) | TWA                                 | 10 mg/m3               | Inhalable fraction.         |
| Portland Cement (CAS 65997-15-1)                   | TWA                                 | 1 mg/m3                | Respirable fraction.        |
| Silica Sand (CAS<br>14808-60-7)                    | TWA                                 | 0.025 mg/m3            | Respirable fraction.        |
| Titanium dioxide (CAS 13463-67-7)                  | TWA                                 | 10 mg/m3               |                             |
| US. NIOSH: Pocket Guide                            | to Chemical Hazards                 |                        |                             |
| Components   | Туре                                | Value                  | Form                        |
| Calcium sulfate dihydrate (CAS 13397-24-5)         | TWA                                 | 5 mg/m3                | Respirable.                 |
| •  |                                     | 10 mg/m3               | Total                       |
| Portland Cement (CAS 65997-15-1)                   | TWA                                 | 5 mg/m3                | Respirable.                 |
|  |                                     | 10 mg/m3               | Total                       |
| Silica Sand (CAS<br>14808-60-7)                    | TWA                                 | 0.05 mg/m3             | Respirable dust.            |
| ogical limit values                                | No biological exposure limits noted | for the ingredient(s). |                             |
| osure guidelines                                   | Occupational exposure to nuisance   |                        | spirable crystalline silica |

DRYTEK Levelex DL SDS US

should be monitored and controlled.

# Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection Wear a dust mask if dust is generated above exposure limits. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** 

Solid. Physical state Powder. **Form** Color Grav. Odorless. Odor **Odor threshold** Not available. Not available. pН Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Flash point Not flammable or combustible.

**Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

Flammability limit - upper

(%)

Not available.

Vapor pressure Not available. Not available. Vapor density Relative density Not available.

Solubility(ies)

Insoluble Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature Viscosity** Not available.

#### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

DRYTEK Levelex DL SDS US 917568 Version #: 02 Revision date: 08-August-2016 Issue date: 05-June-2014

No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation

Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet Skin contact

cement/mixture may cause burns.

Eve contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Ingestion Swallowing may cause gastrointestinal irritation.

Symptoms related to the physical, chemical and toxicological characteristics Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Information on toxicological effects

**Acute toxicity** May cause respiratory irritation.

Components **Species** Test Results Lithium Carbonate (CAS 554-13-2)

Acute

Inhalation

Rat LC50 > 2.17 mg/l, 4 Hours

Oral

LD50 Rat 525 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute

Inhalation

LC50 Rat > 2.28 mg/l, 4 Hours

Oral

LD50 Rat > 11000 mg/kg

Causes skin irritation. Skin corrosion/irritation

Serious eve damage/eve

irritation

Causes serious eye damage.

Respiratory or skin sensitization

No data available. Respiratory sensitization

May cause an allergic skin reaction. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded Carcinogenicity

that crystalline silica inhaled from occupational sources can cause lung cancer in humans.

However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer

risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Silica Sand (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

DRYTEK Levelex DL SDS US **Reproductive toxicity** May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

**Aspiration hazard**Due to the physical form of the product it is not an aspiration hazard.

**Chronic effects** Prolonged or repeated exposure may cause lung injury, including silicosis.

## 12. Ecological information

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

Components Species Test Results

Calcium sulfate dihydrate (CAS 13397-24-5)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Lithium Carbonate (CAS 554-13-2)

Aquatic

Fish LC50 Mummichog (Fundulus heteroclitus) 8.1 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil The product is not mobile in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

DRYTEK Levelex DL SDS US

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US** state regulations

WARNING: This product contains chemical(s) known to the State of California to cause birth

defects or other reproductive harm.

#### **US. Massachusetts RTK - Substance List**

Calcium sulfate dihydrate (CAS 13397-24-5) Calcium sulfate hemihydrate (CAS 10034-76-1)

Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

#### US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate dihydrate (CAS 13397-24-5)

Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate dihydrate (CAS 13397-24-5)

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

#### **US. Rhode Island RTK**

Lithium Carbonate (CAS 554-13-2)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lithium Carbonate (CAS 554-13-2) Silica Sand (CAS 14808-60-7) Titanium dioxide (CAS 13463-67-7)

#### International Inventories

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |

DRYTEK Levelex DL SDS US

Country(s) or region Inventory name On inventory (yes/no)\*

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL) Yes

New ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesNo

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 05-June-2014 **Revision date** 08-August-2016

Version # 02

**NFPA** ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

**Disclaimer** The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

DRYTEK Levelex DL SDS US