

# **SAFETY DATA SHEET**

### 1. Identification

Product identifier Grout Haze Remover

Other means of identification None.

Recommended use Removal of cement-based grout haze from stone & tile surfaces.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

LATICRETE International

Address

1 Laticrete Park, N

1 Laticrete Park, N Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1B

Serious eye damage/eye irritation Category 1

**Environmental hazards** Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects.

**Precautionary statement** 

**Prevention** Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face

protection. Wash thoroughly after handling. Avoid release to the environment.

**Response** If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Category 3

Continue rinsing. Immediately call a poison center/doctor.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
2-Aminoethanol	141-43-5	1 - 5

Grout Haze Remover SDS US

923975 Version #: 01 Revision date: - Issue date: 22-December-2014

Alcohol Ethoxylate	Trade Secret	1 - 5
Dipropylene glycol butyl ether	29911-28-2	1 - 5
Ethoxylated Quaternary Amine	Trade Secret	1 - 5

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention immediately.

Eve contact

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Get medical attention.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed **General information** 

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Permanent eye damage including blindness could result. Headaches, nausea and vomiting.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

General fire hazards

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS. Avoid release to the environment. Do not discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

# 7. Handling and storage

Precautions for safe handling

Avoid inhalation of vapors and contact with skin, eyes and clothing. Use with adequate ventilation. Do not taste or swallow. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool and well-ventilated place. Protect from freezing. Store away from incompatible materials (See Section 10).

Grout Haze Remover SDS US

# 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
2-Aminoethanol (CAS 141-43-5)	PEL	6 mg/m3	
,		3 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
2-Aminoethanol (CAS 141-43-5)	STEL	6 ppm	
,	TWA	3 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
2-Aminoethanol (CAS 141-43-5)	STEL	15 mg/m3	
,		6 ppm	
	TWA	8 mg/m3	
		3 ppm	

Biological limit values

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

No biological exposure limits noted for the ingredient(s).

Skin protection

Respiratory protection

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear appropriate chemical resistant clothing. Frequent change of gloves is advisable.

The world have add when a proposition thermal protective elething, when necessary

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment.

equipment to remove contaminants.

### 9. Physical and chemical properties

Appearance Light yellow liquid.

Physical stateLiquid.FormLiquid.ColorLight yellow.

Odor Mild.

Odor thresholdNot available.pH11.5 - 12.5Melting point/freezing pointNot available.Initial boiling point and boiling212 °F (100 °C)

range

212 1 (100 0

Flash point Does not flash
Evaporation rate Not available.
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

Revision date: -

(%)

923975 Version #: 01

Grout Haze Remover SDS US

Issue date: 22-December-2014

Flammability limit - upper

(%)

Not available.

1.003

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available.

Vapor pressure Not available. Not available. Vapor density

Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available.

> 392 °F (> 200 °C) **Decomposition temperature Viscosity** No data available.

Other information

VOC (Weight %) 2.8 %

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat, flames and sparks. Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition

products

Carbon dioxide. Carbon monoxide. Nitrogen oxides.

# 11. Toxicological information

### Information on likely routes of exposure

Inhalation In high concentrations, vapors may be irritating to the respiratory system.

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage. May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Permanent eye damage including blindness could result. Headaches, nausea and vomiting.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components **Species Test Results** 2-Aminoethanol (CAS 141-43-5) Acute Dermal Rabbit LD50 1025 mg/kg Oral LD50 Rat 1715 mg/kg Alcohol Ethoxylate (CAS Trade Secret) Acute

Dermal

LD50 Rabbit 200 - 5000 mg/kg

Oral

Rat LD50 1100 mg/kg

Grout Haze Remover SDS US

923975 Version #: 01 Issue date: 22-December-2014 Revision date: -

Components Species Test Results

Ethoxylated Quaternary Amine (CAS Trade Secret)

Acute

Oral

LD50 Rat 580 mg/kg

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization Not a skin sensitizer.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity
Specific target organ toxicity -

No data available.

No data available.

single exposure

Specific target organ toxicity - repeated exposure

No data available.

Aspiration hazard Not classified.

Chronic effects Prolonged or repeated contact may dry skin and cause dermatitis. May cause damage to liver and

kidney.

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	lest Results
2-Aminoethanol (CAS	141-43-5)		
Aquatic			
Algae	EC50	Selenastrum capricornutum (new name Pseudokirchnerella subca	2.5 mg/l, 48 hours
Crustacea	EC50	Daphnia magna	65 mg/l, 48 hours
Fish	LC50	Cyprinus carpio	349 mg/l, 96 hours

Persistence and degradability

The product is readily biodegradable.

**Bioaccumulative potential**Not likely to bioaccumulate in aquatic organisms.

Partition coefficient n-octanol / water (log Kow)

2-Aminoethanol (CAS 141-43-5) -1.31

Mobility in soil Not available.

Other adverse effects The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic

organisms.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Tast Dasults

regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Grout Haze Remover SDS US

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

# 14. Transport information

DOT

UN2491 **UN** number

**UN** proper shipping name Ethanolamine solutions

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Ш Packing group

**Environmental hazards** 

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB3, T4, TP1 **Special provisions** 

154 Packaging exceptions 203 Packaging non bulk Packaging bulk 241

**IATA** 

**UN** number UN2491

UN proper shipping name Ethanolamine solution

Transport hazard class(es) 8 Class Subsidiary risk Packing group Ш **Environmental hazards** No

**ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN** number UN2491

ETHANOLAMINE SOLUTION **UN** proper shipping name

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** 

Marine pollutant No **EmS** F-A. S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

**General information** IATA classification is not relevant as the material is not transported by air.

# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910,1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not available.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SDS US Grout Haze Remover

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

# SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations**This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

#### **US. Massachusetts RTK - Substance List**

2-Aminoethanol (CAS 141-43-5)

### US. New Jersey Worker and Community Right-to-Know Act

2-Aminoethanol (CAS 141-43-5)

### US. Pennsylvania Worker and Community Right-to-Know Law

2-Aminoethanol (CAS 141-43-5)

#### **US. Rhode Island RTK**

Not regulated.

### **US. California Proposition 65**

Not Listed.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 22-December-2014

Revision date - 01

Grout Haze Remover SDS US

923975 Version #: 01 Revision date: - Issue date: 22-December-2014

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# **NFPA** ratings



# List of abbreviations

References

HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer

The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.

Grout Haze Remover SDS US