



STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 05/05/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Substance

Product Name: STONETECH® Honing Powder 400 Grit

1.2. Intended Use of the Product

Refinishing calcium based stones. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

(833)-254-9255

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Not classified

2.2. Label Elements

GHS-US/CA Labeling

No labeling applicable according to 29 CFR 1910.1200 and the Hazardous Products Regulations (HPR) SOR/2015-17.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Name : STONETECH® Honing Powder 400 Grit

| Name | Product Identifier | % * | GHS Ingredient Classification |
|--|---------------------|-----|-------------------------------|
| Aluminum oxide (Al ₂ O ₃) | (CAS-No.) 1344-28-1 | 100 | Not classified |

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

3.2. Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Metallic oxides.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Refinishing calcium based stones. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Aluminum oxide (Al ₂ O ₃) (1344-28-1) | | |
|--|-------------------------------------|--|
| USA ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| Alberta | OEL TWA (mg/m ³) | 10 mg/m ³ |
| New Brunswick | OEL TWA (mg/m ³) | 10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL STEL (mg/m ³) | 20 mg/m ³ |
| Nunavut | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Northwest Territories | OEL STEL (mg/m ³) | 20 mg/m ³ |
| Northwest Territories | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Québec | VEMP (mg/m ³) | 10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust) |
| Saskatchewan | OEL STEL (mg/m ³) | 20 mg/m ³ |
| Saskatchewan | OEL TWA (mg/m ³) | 10 mg/m ³ |
| Yukon | OEL STEL (mg/m ³) | 20 mg/m ³ (Al ₂ O ₃) |
| Yukon | OEL TWA (mg/m ³) | 30 mppcf (Al ₂ O ₃) 10 mg/m ³ (Al ₂ O ₃) |

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

| | |
|----------------|---------|
| Physical State | : Solid |
| Appearance | : White |
| Odor | : None |

STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--|--------------------|
| Odor Threshold | : Not available |
| pH | : Not available |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : Not available |
| Flash Point | : Not available |
| Auto-ignition Temperature | : Not available |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20°C | : Not available |
| Relative Density | : Not available |
| Specific Gravity | : 3.8 |
| Solubility | : Water: Insoluble |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

- Acute Toxicity (Oral):** Not classified
- Acute Toxicity (Dermal):** Not classified
- Acute Toxicity (Inhalation):** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Not classified
- Eye Damage/Irritation:** Not classified
- Respiratory or Skin Sensitization:** Not classified
- Germ Cell Mutagenicity:** Not classified
- Carcinogenicity:** Not classified
- Specific Target Organ Toxicity (Repeated Exposure):** Not classified
- Reproductive Toxicity:** Not classified
- Specific Target Organ Toxicity (Single Exposure):** Not classified
- Aspiration Hazard:** Not classified
- Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.
- Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.
- Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.
- Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.
- Chronic Symptoms:** None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Aluminum oxide (Al₂O₃) (1344-28-1)

STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|---------------------|---------------|
| LD50 Oral Rat | > 15900 mg/kg |
| LC50 Inhalation Rat | > 2.3 mg/l/4h |

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

| | |
|--|------------|
| Aluminum oxide (Al ₂ O ₃) (1344-28-1) | |
| LC50 Fish 1 | > 100 mg/l |
| EC50 Daphnia 1 | > 100 mg/l |
| ErC50 (algae) | > 100 mg/l |
| NOEC (Acute) | > 50 mg/l |

12.2. Persistence and Degradability

| | |
|-----------------------------------|------------------|
| STONETECH® Honing Powder 400 Grit | |
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| | |
|-----------------------------------|------------------|
| STONETECH® Honing Powder 400 Grit | |
| Bioaccumulative Potential | Not established. |

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| | |
|--|---------------------|
| Aluminum oxide (Al ₂ O ₃) (1344-28-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| SARA Section 313 - Emission Reporting | 1 % (fibrous forms) |

15.2. US State Regulations

| |
|---|
| Aluminum oxide (Al ₂ O ₃) (1344-28-1) |
| U.S. - Massachusetts - Right To Know List |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |
| U.S. - Pennsylvania - RTK (Right to Know) List |

15.3. Canadian Regulations

| |
|--|
| Aluminum oxide (Al ₂ O ₃) (1344-28-1) |
| Listed on the Canadian DSL (Domestic Substances List) |

STONETECH® Honing Powder 400 Grit

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 05/05/2020

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)