

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 10/23/2018 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier Product Form: Mixture

Product Name: L&M™ Durapatch Industrial™

1.2. Intended Use of the Product

Patching. For professional use only

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

 Bethany, CT 06524
 NOR-1A0

 T (203)-393-0010
 (833)-254-9255

 www.laticrete.com
 www.laticrete.com

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency Call CHEMTREC day or night

Within USA and Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

 Skin Corr. 1C
 H314

 Eye Dam. 1
 H318

 Skin Sens. 1
 H317

 Carc. 1A
 H350

 STOT SE 3
 H335

 STOT RE 1
 H372

 Aquatic Acute 3
 H402

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)







Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H350 - May cause cancer (Inhalation).

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

H402 - Harmful to aquatic life.

Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

10/23/2018 EN (English US) 1/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Quartz	(CAS-No.) 14808-60-7	41.7 - 42.5	Carc. 1A, H350
			STOT SE 3, H335
			STOT RE 1, H372
Cement, portland, chemicals	(CAS-No.) 65997-15-1	15 - 40	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			STOT SE 3, H335
Calcium oxide	(CAS-No.) 1305-78-8	21 - 26	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 3, H402
Calcium sulfate hemihydrate	(CAS-No.) 10034-76-1	17.1 - 19	Not classified
Limestone	(CAS-No.) 1317-65-3	<= 2	Not classified
Calcium sulfate dihydrate	(CAS-No.) 13397-24-5	<= 2	Not classified
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	<= 2	Not classified
Silicic acid (H4SiO4), calcium salt (1:2)	(CAS-No.) 10034-77-2	1.1 - 1.8	Eye Irrit. 2A, H319
Diatomaceous earth	(CAS-No.) 61790-53-2	< 0.1	Not classified
Formaldehyde	(CAS-No.) 50-00-0	< 0.0008	Flam. Liq. 4, H227
			Acute Tox. 3 (Oral), H301
			Acute Tox. 3 (Dermal), H311
			Acute Tox. 3 (Inhalation:gas), H331
			Skin Corr. 1B, H314
			Eye Dam. 1, H318

10/23/2018 EN (English US) 2/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Skin Sens. 1, H317
			Muta. 2, H341
			Carc. 1A, H350
			STOT SE 3, H335
			Aquatic Acute 2, H401
Chromium, ion (Cr6+)	(CAS-No.) 18540-29-9	< 0.00004	Skin Sens. 1, H317
			Carc. 1B, H350
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Skin sensitization. Causes severe skin burns and eye damage.

Inhalation: Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Skin Contact: When this product is wet it is corrosive. Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. May cause cancer by inhalation.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Silicon oxides. Carbon oxides (CO, CO₂). Sulfur oxides. Calcium oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

10/23/2018 EN (English US) 3/14

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

^{**} The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Cautiously neutralize spilled solid. Recover the product by vacuuming, shoveling or sweeping. Minimize generation of dust. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May release corrosive vapors.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

7.3. Specific End Use(s)

Patching. For professional use only

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)

10/23/2018 EN (English US) 4/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

According to rederal Register / Vol. 77, No		According to the Hazardous Products Regulation (February 11, 2015).
USA IDLH	US IDLH (mg/m³)	50 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
Nunavut	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Ontario	OEL TWA (mg/m³)	0.1 mg/m³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
Québec	VEMP (mg/m³)	0.1 mg/m³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	300 particle/mL
Cement, portland, chemicals	, . ,	
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (particulate matter containing no asbestos and
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
	(, (, ,)	5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
	(, , , , , , , , , , , , , , , , , , ,	5 mg/m³ (respirable dust)
USA IDLH	US IDLH (mg/m³)	5000 mg/m³
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and
	322 : *** (g/ /	<1% Crystalline silica-respirable particulate)
Manitoba	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-particulate matter, respirable
		particulate matter)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (particulate matter containing no Asbestos and
	, ,	<1% Crystalline silica)
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and
	, ,	<1% Crystalline silica-particulate matter, respirable
		particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-particulate matter, respirable
		particulate matter)
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-respirable)
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-particulate matter, respirable
		particulate matter)
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
		5 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-respirable dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
	•	· · · · · · · · · · · · · · · · · · ·

10/23/2018 EN (English US) 5/14

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		According to the Hazardous Products Regulation (February 11, 2015).
Yukon	OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m ³
Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³
USA IDLH	US IDLH (mg/m³)	25 mg/m³
Alberta	OEL TWA (mg/m³)	2 mg/m³
British Columbia	OEL TWA (mg/m³)	2 mg/m³
Manitoba	OEL TWA (mg/m³)	2 mg/m³
New Brunswick	OEL TWA (mg/m³)	2 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³
Nunavut	OEL STEL (mg/m³)	4 mg/m³
Nunavut	OEL TWA (mg/m³)	2 mg/m³
Northwest Territories	OEL STEL (mg/m³)	4 mg/m³
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³
Ontario	OEL TWA (mg/m³)	2 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³
Québec	VEMP (mg/m³)	2 mg/m³
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³
Yukon	OEL STEL (mg/m³)	4 mg/m³
Yukon	OEL TWA (mg/m³)	2 mg/m³
Limestone (1317-65-3)	, , ,	
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
		5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
	, , , ,	5 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m ³
British Columbia	OEL STEL (mg/m³)	20 mg/m³ (total dust)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
	, ,	3 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (particulate matter containing no Asbestos and
	, ,	<1% Crystalline silica)
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m³)	10 mg/m³ (Limestone, containing no Asbestos and <1%
		Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m³
Magnesium oxide (MgO) (13	309-48-4)	
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (fume, total particulate)
	US IDLH (mg/m³)	

10/23/2018 EN (English US) 6/14

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		T
Alberta	OEL TWA (mg/m³)	10 mg/m³ (fume)
British Columbia	OEL STEL (mg/m³)	10 mg/m³ (respirable dust and fume)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (fume, inhalable)
		3 mg/m³ (respirable dust and fume)
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (fume)
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Ontario	OEL TWA (mg/m³)	10 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	10 mg/m³ (fume)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	10 mg/m³ (fume)
Yukon	OEL TWA (mg/m³)	10 mg/m³ (fume)
Chromium, ion (Cr6+) (1854		
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 μg/m³
Calcium sulfate hemihydrate		1 × 100 ···
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Manitoba	OEL TWA (mg/m²)	10 mg/m³ (inhalable particulate matter)
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m³ (inhalable particulate matter)
Ontario	OEL TWA (IIIg/III) OEL TWA (IIIg/III)	10 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m³ (inhalable particulate matter)
	OLL TWA (IIIg/III)	10 mg/m (minarable particulate matter)
Formaldehyde (50-00-0)	ACCILL TIA/A (acces)	0.4
USA ACGIH	ACCILISTEL (name)	0.1 ppm
USA ACGIH	ACCIU shaminal actors a	0.3 ppm
USA ACGIH	ACGIH chemical category	dermal sensitizer,Confirmed Human Carcinogen
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)
USA NIOSH	NIOSH REL (TWA) (ppm)	0.016 ppm
USA NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm
USA IDLH	US IDLH (ppm)	20 ppm
Alberta	OEL Ceiling (mg/m³)	1.3 mg/m³
Alberta	OEL TWA (mg/m³)	1 ppm
Alberta	OEL TWA (mg/m³)	0.9 mg/m³
Alberta	OEL TWA (ppm)	0.75 ppm
British Columbia	OEL Ceiling (ppm)	1 ppm
British Columbia	OEL TWA (ppm)	0.3 ppm
Manitoba	OEL STEL (ppm)	0.3 ppm
Manitoba	OEL TWA (ppm)	0.1 ppm
New Brunswick	OEL STEL (ppm)	1.5 ppm
New Brunswick	OEL TWA (ppm)	0.5 ppm
Newfoundland & Labrador	OEL STEL (ppm)	0.3 ppm
Newfoundland & Labrador	OEL TWA (ppm)	0.1 ppm
Nova Scotia	OEL STEL (ppm)	0.3 ppm
Nova Scotia	OEL TWA (ppm)	0.1 ppm

10/23/2018 EN (English US) 7/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

NI	OFI Calling (anna)	0.3
Nunavut	OEL Ceiling (ppm)	0.3 ppm
Northwest Territories	OEL Ceiling (ppm)	0.3 ppm
Ontario	OEL Ceiling (ppm)	1.5 ppm
Ontario	OEL STEL (ppm)	1 ppm
Prince Edward Island	OEL STEL (ppm)	0.3 ppm
Prince Edward Island	OEL TWA (ppm)	0.1 ppm
Québec	PLAFOND (mg/m³)	3 mg/m ³
Québec	PLAFOND (ppm)	2 ppm
Saskatchewan	OEL Ceiling (ppm)	0.3 ppm
Yukon	OEL Ceiling (mg/m³)	3 mg/m³
Yukon	OEL Ceiling (ppm)	2 ppm
Diatomaceous earth (61790	-53-2)	
British Columbia	OEL TWA (mg/m³)	4 mg/m³ (total)
		1.5 mg/m³ (respirable)
New Brunswick	OEL TWA (mg/m³)	3 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable fraction)
		10 mg/m³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, inhalable fraction)
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
		6 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
		3 mg/m³ (respirable fraction)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
		6 mg/m³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
		3 mg/m³ (respirable fraction)
Québec	VEMP (mg/m³)	6 mg/m³ (containing no Asbestos and <1% Crystalline
	27, 277, (2)	silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
	05, 50, 4 (2)	6 mg/m³ (respirable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
		3 mg/m³ (respirable fraction)
Calcium sulfate dihydrate (1		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
LICA NUOCII	AUGCII DEL (TIMA) (m (m.3)	5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
Alberta	OEL TWA (mg/m³)	5 mg/m³ (respirable dust) 10 mg/m³
British Columbia	OEL TWA (mg/m³) OEL STEL (mg/m³)	20 mg/m³ (total dust)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
Diffish Columbia	OLL TWA (IIIg/III)	3 mg/m³ (respirable fraction)
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Newfoundland & Labrador	OEL TWA (IIIg/III) OEL TWA (IIIg/III)	10 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m³ (inhalable particulate matter)
Ontario	OEL TWA (mg/m ³)	10 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline
Quenec	V LIVII (IIIB/III)	silica-total dust)
		5 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-respirable dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Justice Trail	JEE 31EE (1116/1117)	יי וסייי כ

10/23/2018 EN (English US) 8/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.











Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield. **Skin and Body Protection:** Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1.	Information on	Rasic Physical a	and Chemical	Properties
J.1.	IIIIOI IIIauoii oii	Dasic Pilvsical (anu Chemicai	riobeilles

Physical State : Solid

Appearance : Grey powder

Odor : None

Odor Threshold:Not availablepH:Not availableEvaporation Rate:Not availableMelting Point:Not availableFreezing Point:Not availableBoiling Point:Not availableFlash Point:Not available

Auto-ignition Temperature Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available Upper Flammable Limit Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C Not available **Relative Density** Not available

Specific Gravity : 2.65

Solubility: Insoluble in waterPartition Coefficient: N-Octanol/Water: Not availableViscosity: Not available

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.
- 10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

10/23/2018 EN (English US) 9/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- **10.5. Incompatible Materials:** Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.
- **10.6. Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: When this product is wet it is corrosive. Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. **Chronic Symptoms:** Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects. May cause cancer by inhalation.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Calcium oxide (1305-78-8)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg
Magnesium oxide (MgO) (1309-48-4)	
LD50 Oral Rat	3870 mg/kg
Formaldehyde (50-00-0)	
LD50 Oral Rat	100 mg/kg
LD50 Dermal Rat	270 mg/kg
ATE US/CA (gas)	700.00 ppmV/4h
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Chromium, ion (Cr6+) (18540-29-9)	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

10/23/2018 EN (English US) 10/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Formaldehyde (50-00-0)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.
Diatomaceous earth (61790-53-2)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life.

Calcium oxide (1305-78-8)	
LC50 Fish 1	50.6 mg/l
Chromium, ion (Cr6+) (18540-29-9)	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Formaldehyde (50-00-0)	
LC50 Fish 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1510 μg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and Degradability

L&M™ Durapatch Industrial™	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

L&M™ Durapatch Industrial™	
Bioaccumulative Potential	Not established.
Calcium oxide (1305-78-8)	
BCF Fish 1	(no bioaccumulation)
Formaldehyde (50-00-0)	
Log Pow	0.35 (at 25 °C)

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport
 14.2. In Accordance with IMDG Not regulated for transport
 14.3. In Accordance with IATA Not regulated for transport
 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

L&M™ Durapatch Industrial™	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated

10/23/2018 EN (English US) 11/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

exposure)
Health hazard - Carcinogenicity
Health hazard - Respiratory or skin sensitization
Health hazard - Serious eye damage or eye irritation
Health hazard - Skin corrosion or Irritation

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Formaldehyde (50-00-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 313 - Emission Reporting	0.1 %

Diatomaceous earth (61790-53-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Chromium, ion (Cr6+) (18540-	X	Х		
29-9)				
Formaldehyde (50-00-0)	Х			

Quartz (14808-60-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Cement, portland, chemicals (65997-15-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium oxide (1305-78-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

10/23/2018 EN (English US) 12/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Pennsylvania - RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Chromium, ion (Cr6+) (18540-29-9)

- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Formaldehyde (50-00-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Diatomaceous earth (61790-53-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

Calcium sulfate dihydrate (13397-24-5)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List)

Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Listed on the Canadian DSL (Domestic Substances List)

Formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

Diatomaceous earth (61790-53-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Calcium sulfate dihydrate (13397-24-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision

Other Information

- : 10/23/2018
- : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2

10/23/2018 EN (English US) 13/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Muta. 2	Germ cell mutagenicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

10/23/2018 EN (English US) 14/14