LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier L&M Lumiseal Plus

Other means of identification None.

Recommended use Sealer.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

LATICRETE International

Address

1 Laticrete Park, N

1 Laticrete Park, N Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night USA/Canada - 1.800.424.9300

Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Aspiration hazard

Not classified.

Category 1

Category 2

Environmental hazards Hazardous to the aquatic environment.

long-term hazard

OSHA defined hazards

Label elements



Signal word Dange

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause

respiratory irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long

lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately

call a poison center/doctor. Do not induce vomiting. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	% 11 - 14	
Solvent naphtha (petroleum), light aromatic	64742-95-6		
1,2,4-Trimethylbenzene	95-63-6	6 - 11	
Xylene	1330-20-7	0.5 - 3.5	
Solvent naphtha (petroleum), medium aliph.	64742-88-7 0.4 - 0.6		
Cumene	98-82-8	0 - 0.65	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

Skin contact

Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical

attention if irritation develops and persists.

Eye contact

Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to

do. Get medical attention immediately.

Ingestion

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Irritating to eyes, respiratory system and skin. Irritation of nose and throat. Irritating to mucous membranes.

Indication of immediate medical attention and special treatment needed

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

General fire hazards

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

TWA

Components	Туре	Value	
Cumene (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
1,2,4-Trimethylbenzene	TWA	25 ppm	
(CAS 95-63-6)			
Cumene (CAS 98-82-8)	TWA	50 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
Cumene (CAS 98-82-8)	TWA	245 mg/m3	
,		50 ppm	
Xylene (CAS 1330-20-7)	STEL	655 mg/m3	
, (,	-	150 ppm	
		100 PP///	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
* - For sampling details, please see the source document.				

435 mg/m3

100 ppm

L&M Lumiseal Plus SDS US

923866 Version #: 01 Revision date: - Issue date: 26-November-2014

Exposure guidelines Follow standard monitoring procedures.

US - California OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear goggles/face shield.

Skin protection

Hand protection Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is

advisable. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves.

Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that

is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory

equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Appearance Clear liquid.
Physical state Liquid.
Form Liquid.
Color Clear.

Odor Aromatic solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not applicable.

Initial boiling point and boiling 326 - 348 °F (163.33 - 175.56 °C)

range

Flash point 112.0 °F (44.4 °C) Tag Closed Cup

Evaporation rate Not applicable.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits
Flammability limit - lower 1 %

(%)

Flammability limit - upper 7 %

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%)Not available.Vapor pressure2.6 mm HgVapor densityNot available.

Relative density 0.93

Solubility(ies)

Solubility (water) Insoluble in water.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition. Stable at normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition Carbon monoxide. Carbon dioxide. Sulfur oxides. Nitrogen oxides. Hydrocarbons.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause respiratory irritation.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Irritating to eyes, respiratory system and skin. Irritation of nose and throat. Irritating to mucous

> 5000 mg/kg

membranes.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

· · · · · · · · · · · · · · · · · · ·		
Components	nents Species Test Results	
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	2910 mg/kg
Solvent naphtha (petroleun	n), medium aliph. (CAS 64742-88-7)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		

L&M Lumiseal Plus SDS US

irritation

LD50

Skin corrosion/irritation

Serious eye damage/eye

Causes skin irritation.

Causes serious eye irritation.

Rat

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Not classified.

Carcinogenicity Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cumene (CAS 98-82-8) 2B Possibly carcinogenic to humans.

May cause respiratory irritation.

Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Further information Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components Species Test Results

1,2,4-Trimethylbenzene (CAS 95-63-6)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

Cumene (CAS 98-82-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.7 mg/l, 96 hours

(Oncorhynchus mykiss)

Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)

Aquatic

Acute

Crustacea EL50 Daphnia 4.5 mg/l, 48 hours Fish LL50 Oncorhynchus mykiss 10 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available for this product.

Mobility in soil

No data available.

Mobility in general

The product is insoluble in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not

incinerate sealed containers. Do not allow this material to drain into sewers/water supplies.

Dispose in accordance with all applicable regulations.

used.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging

Hazardous waste code

Dispose of in accordance with local regulations. Empty containers should be taken to an approved

Waste codes should be assigned by the user based on the application for which the product was

waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1268

UN proper shipping name Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, B1, IB3, T4, TP1, TP29

Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1268

UN proper shipping name Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards Yes
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1268

UN proper shipping name Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

Marine pollutant Yes
EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. **This substance/mixture is not intended to be transported in bulk.**

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

....

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) LISTED Xylene (CAS 1330-20-7) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

L&M Lumiseal Plus SDS US

923866 Version #: 01 Revision date: - Issue date: 26-November-2014

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-Trimethylbenzene	95-63-6	6 - 11	
Xylene	1330-20-7	0.5 - 3.5	
Cumene	98-82-8	0 - 0.65	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)

Cumene (CAS 98-82-8) Xylene (CAS 1330-20-7)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Cumene (CAS 98-82-8) Ethylbenzene (CAS 100-41-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

L&M Lumiseal Plus SDS US 8/9

923866 Version #: 01 Revision date: - Issue date: 26-November-2014

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 26-November-2014

Revision date - Version # 01

NFPA ratings



List of abbreviations

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.