LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier LATAPOXY 210 Adhesive Part B

Other means of identification None.

Recommended use Adhesive.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor informationCompany NameLATICRETE InternationalAddress1 Laticrete Park, N

Bethany, CT 06524

Telephone(203)-393-0010Contact personSteve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

Label elements

Environmental hazards



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to

aquatic life with long lasting effects.

Precautionary statement

Prevention Wear protective gloves and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Avoid release to the environment.

Response IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

LATAPOXY 210 Adhesive Part B SDS Canada

917013 Version #: 01 Revision date: - Issue date: 19-October-2016

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propane, 2,2-bis[p-(2,3-epoxypropoxy)ph enyl]-, polymers	25085-99-8	17-20
Bisphenol F epoxy resin	9003-36-5	3 - 5
Alkyl(C12-14) glycidyl ether	68609-97-2	1-3

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash, Irritant effects.

Indication of immediate medical attention and special

treatment needed General information Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

contaminated clothing before reuse.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all releases.

LATAPOXY 210 Adhesive Part B SDS Canada

7. Handling and storage

Precautions for safe handling Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Persons with epoxy

allergy should not work with this product. Wear appropriate personal protective equipment. Provide

adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection

No exposure limits noted for ingredient(s). Occupational exposure limits

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Exposure guidelines No exposure standards allocated.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Off-white. Color Not available. Odor Not available. **Odor threshold**

9 - 10 Ha 32 °F (0 °C) Melting point/freezing point Initial boiling point and boiling 413.6 °F (212 °C)

range

Non flammable. Flash point **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapor pressure Not available. Not available. Vapor density

1 Relative density

Solubility(ies)

Solubility (water) Soluble Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature**

LATAPOXY 210 Adhesive Part B SDS Canada **Decomposition temperature** Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

Masses of more than 1 pound of product plus an aliphatic amine will cause irreversible polymerization with considerable heat build up.

reactions

Excessive heat. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactIrritating to skin. May cause an allergic skin reaction.

Eye contact Irritating to eyes.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Rash. Irritant effects.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components Species Test Results

Bisphenol F epoxy resin (CAS 9003-36-5)

Acute Dermal

LD50 Rat > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not expected to be mutagenic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

No data available.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard No data available.

Chronic effects Prolonged or repeated contact may cause drying, cracking, or irritation.

Further information No other specific acute or chronic health impact noted.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

LATAPOXY 210 Adhesive Part B SDS Canada

Species Test Results Components

Bisphenol F epoxy resin (CAS 9003-36-5)

Aquatic

Acute

LC50 Fish Leuciscus idus 5.7 mg/l, 96 hours

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers (CAS 25085-99-8)

Aquatic

Acute

Algae IC50 11 mg/l, 72 hours Algae EC50 1.8 mg/l, 48 hours Crustacea Daphnia

Fish LC50 Fish 1 - 10 ma/l

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available for this product.

Mobility in soil

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG

UN3082 **UN number**

Environmentally hazardous substance, liquid, n.o.s. (Propane, **UN proper shipping name**

2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, Bisphenol F epoxy resin)

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group D **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN3082

Environmentally hazardous substance, liquid, n.o.s. (Propane, **UN proper shipping name**

2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, Bisphenol F epoxy resin)

Transport hazard class(es)

LATAPOXY 210 Adhesive Part B

9 **Class** Subsidiary risk 9 Label(s) Ш Packing group **Environmental hazards** Yes **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number

Environmentally hazardous substance, liquid, n.o.s. (Propane, **UN proper shipping name**

2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, Bisphenol F epoxy resin)

Transport hazard class(es)

9 Class Subsidiary risk Label(s) 9 Packing group Ш

Environmental hazards

Marine pollutant Yes F-A, S-F **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not available.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS **Canadian regulations**

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

United States & Puerto Rico

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

LATAPOXY 210 Adhesive Part B SDS Canada

917013 Version #: 01 Revision date: -Issue date: 19-October-2016 Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 19-October-2016

Revision date - 01

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATAPOXY 210 Adhesive Part B SDS Canada