LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE® 125 Sound & Crack Adhesive

Other means of identification None.

Recommended use Adhesive.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name LATICRETE International

Address 1 Laticrete Park, N

Bethany, CT 06524

Telephone(203)-393-0010Contact personSteve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 2

Specific target organ toxicity following single Category 3 respiratory tract irritation

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

Suspected of causing cancer. May cause respiratory irritation.

Precautionary statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTRE or

doctor/physician.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

LATICRETE® 125 Sound & Crack Adhesive 917125 Version #: 01 Revision date: - Issue date: 20-June-2017 **Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Not classified.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Portland Cement	65997-15-1	35 - 40	
Carbon black	1333-86-4	8 - 11	
Calcium formate	544-17-2	1 - 2	
Zinc oxide	1314-13-2	0.08 - 0.15	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

centre immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed
General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

flush area with water

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)	STEL TWA	10 mg/m3 2 mg/m3	Respirable fraction. Respirable fraction.
Canada Albarta OELa (Occupatio		_	
Canada. Alberta OELs (Occupation Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	
Zinc oxide (CAS 1314-13-2)	STEL TWA	10 mg/m3 2 mg/m3	Respirable. Respirable.
Canada. British Columbia OELs. (ts for Chemical Substances, O	ccupational Health and
Safety Regulation 296/97, as ame	•	Value	Form
Components	Туре		
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable
Portland Cement (CAS 65997-15-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable.
	TWA	2 mg/m3	Respirable.
Canada. Manitoba OELs (Reg. 21) Components	7/2006, The Workplace Safety Type	And Health Act) Value	Form
Carbon black (CAS	TWA	3 mg/m3	Inhalable fraction.
1333-86-4) Portland Cement (CAS	TWA	1 mg/m3	Respirable fraction.
65997-15-1) `		, and the second	•
		10 mg/m3	Respirable fraction.
	STEL	•	
	STEL TWA	2 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)	TWA	2 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control o	TWA	2 mg/m3	Respirable fraction. Form
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control o Components Carbon black (CAS	TWA f Exposure to Biological or C	2 mg/m3 Chemical Agents)	
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS	TWA f Exposure to Biological or C Type	2 mg/m3 Chemical Agents) Value	Form
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1)	TWA f Exposure to Biological or C Type TWA TWA STEL	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2)	TWA f Exposure to Biological or C Type TWA TWA STEL TWA	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Canada)	TWA f Exposure to Biological or C Type TWA TWA STEL TWA	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Components Carbon black (CAS	TWA f Exposure to Biological or C Type TWA TWA STEL TWA TWA of Labor - Regulation respect	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3 ting occupational health and se	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1)	TWA f Exposure to Biological or C Type TWA TWA STEL TWA of Labor - Regulation respect	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3 ting occupational health and selections	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS	TWA f Exposure to Biological or C Type TWA TWA STEL TWA of Labor - Regulation respect Type TWA	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3 ting occupational health and sevalue 3.5 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Form
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1)	TWA f Exposure to Biological or C Type TWA TWA STEL TWA of Labor - Regulation respect Type TWA	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3 ting occupational health and sevalue 3.5 mg/m3 5 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction. afety) Form Respirable dust.
Zinc oxide (CAS 1314-13-2) Canada. Ontario OELs. (Control of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2) Canada. Quebec OELs. (Ministry of Components Carbon black (CAS 1333-86-4) Portland Cement (CAS	TWA f Exposure to Biological or C Type TWA TWA STEL TWA of Labor - Regulation respect Type TWA TWA TWA	2 mg/m3 Chemical Agents) Value 3 mg/m3 1 mg/m3 10 mg/m3 2 mg/m3 ting occupational health and sevalue 3.5 mg/m3 5 mg/m3 10 mg/m3	Form Inhalable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Respirable fraction. Afety) Form Respirable dust. Total dust.

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear chemical-resistant, impervious gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protectionWear a dust mask if dust is generated above exposure limits. **Thermal hazards**Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormPowder.ColourGrey.

Odour Not available.
Odour threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point This product is not flammable or combustible.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Vapour pressure Not available.
Vapour density Not available.

Relative density 0.8

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

LATICRETE® 125 Sound & Crack Adhesive

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials

Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Swallowing may cause gastrointestinal irritation. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Rash. Coughing, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components **Species Test results**

Calcium formate (CAS 544-17-2)

Acute

Oral

LD50 Rat 2650 mg/kg

Carbon black (CAS 1333-86-4)

Acute

Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Respiratory sensitisation No data available.

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

ACGIH Carcinogens

Carbon black (CAS 1333-86-4) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Portland Cement (CAS 65997-15-1) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Carbon black (CAS 1333-86-4) Confirmed animal carcinogen with unknown relevance to humans.

Portland Cement (CAS 65997-15-1) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -No data available.

repeated exposure

Due to the physical form of the product it is not an aspiration hazard. **Aspiration hazard**

Chronic effects Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

LATICRETE® 125 Sound & Crack Adhesive 917125 Version #: 01 Revision date: -Issue date: 20-June-2017

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components Species Test results

Carbon black (CAS 1333-86-4)

Aquatic Acute

Fish LC50 Leuciscus idus >= 1000 mg/l, 96 Hours

Zinc oxide (CAS 1314-13-2)

Aquatic

Crustacea LC50 Water flea (Daphnia magna) 0.098 mg/l, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil The product is not mobile in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Issue date: 20-June-2017

Zinc oxide (CAS 1314-13-2)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

LATICRETE® 125 Sound & Crack Adhesive SDS Canada

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Issue date 20-June-2017

Revision date - 01

United States & Puerto Rico

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE® 125 Sound & Crack Adhesive

SDS Canada

917125 Version #: 01 Revision date: - Issue date: 20-June-2017

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).